

Corrected

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Pottawatomie Fraction SW 1/4 SE 1/4 SE 1/4 NE 1/4 Section Number 24 Township Number T 9 S Range Number R 8 E W

2 WELL OWNER: Last Name: Meyer First: Ben Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: 6810 Hopkins Creek Road Drive

3 LOCATE WELL WITH 'X' IN SECTION BOX: N W E S 1 mile

4 DEPTH OF COMPLETED WELL: 132 ft. Depth(s) Groundwater Encountered: 1) 56 ft. 2) ft. 3) ft. or 4) Dry Well WELL'S STATIC WATER LEVEL: 48 ft. below land surface, measured on (mo-day-yr) 06/17/2019

5 Latitude: 39.2552700 (decimal degrees) Longitude: 96.4656630 (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model) (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper

6 Elevation: 1264 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID Dewatering: how many wells? Aquifer Recharge: well ID Monitoring: well ID Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection Oil Field Water Supply: lease Test Hole: well ID Cased Uncased Geotechnical Geothermal: how many bores? Closed Loop Horizontal Vertical Open Loop Surface Discharge Inj. of Water Other (specify)

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 6 in. to 132 ft. Diameter in. to ft. Diameter in. to ft. Casing height above land surface 24 in. Weight lbs./ft. Wall thickness or gauge No. SCH-40

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Brass Galvanized Steel PVC Other (Specify) None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 72 ft. to 92 ft., From 112 ft. to 132 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 132 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank Lateral Lines Pit Privy Livestock Pen Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? west Distance from well? 15'

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-12 Clay, 12-22 Tan Shale, 22-26 limestone, 26-46 grey shale, 46-49 limestone, 49-56 grey shale, 56-63 weathered Limestone, 63-79 Grey Shale, 79-81 Limestone

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 06/17/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 914 This Water Well Record was completed on (mo-day-year) 07/01/2019 under the business name of Flint Hills Drilling