


1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 SW 1/4 Section Number 32 Township Number T 9 S Range Number R 9 E/W
 County: POTTAWATOMIE

Distance and direction from nearest town or city street address of well if located within city?
4 3/4 south of Flush

2 WATER WELL OWNER: Carl Meyer - Horticultural Services
 RR#, St. Address, Box # : 11524 Landscape Lane Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : St. George, KS 66535 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 175' ft. ELEVATION:ft.
 Depth(s) Groundwater Encountered 1.ft. 2.ft. 3.ft.
 WELL'S STATIC WATER LEVEL ... ~~XXX~~ 100ft. below land surface measured on mo/day/yr 4-30-96
 Pump test data: Well water wasft. after hours pumping gpm
 Est. Yield .70 gpm: Well water wasft. after hours pumping gpm
 Bore Hole Diameter... 12" in. toft., and in. toft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No X.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded.....
 Blank casing diameter 6" in. to 0-163ft., Dia 6" in. toft., Dia in. toft.
 Casing height above land surface 24" in., weight 3.6 lbs./ft. Wall thickness or gauge No.280.....
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 163ft. to 173ft., Fromft. toft.
 From 173ft. to 175ft., Fromft. toft.
 GRAVEL PACK INTERVALS: From 24ft. to 175ft., Fromft. toft.
 Fromft. toft., Fromft. toft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4ft. to 24ft., Fromft. toft., Fromft. toft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage pond.....
 Direction from well? west How many feet? 800'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Clay-Brown-Silty			
8	57	Fine Sand-Brown-Silty			
57	62	Clay-Brown-Silty			
62	78	FS-Brown-Silty			
78	82	Clay-Brown-Silty			
82	100	Fine Sand-Br-Silty			
100	104	Clay-Brown-Silty			
104	110	Fine Sand-Brown-Silty			
110	114	Clay-Brown-Silty			
114	151	Fine Sand-Brown			
151	153	Fine Sand-Coarse Sand-Brown			
153	164	Clay-Brown-Silty			
164	173	Fine Sand-Coarse Sand-Br-Sugar Sand			
173	175	Limestone-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-30-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 5-30-96 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Hester

OFFICE USE ONLY T R E/W SEC. 1/4 1/4 1/4 1/4