WATE	R WEL	L RECORD	Form WWC	C-5	Division of Wat	er Resources; App. No.		
1 LO	CATION (OF WATER WELL:	Fraction		Section Number			
Cou	nty: Osbo	rne	SW 1/4 NE 1/4		17	T 10 S	R 15 E/W	
Į Dist	ance and di	rection from nearest town or cit		vell if		g Systems (decimal deg	grees, min. of 4 digits)	
located within city? N 1st & Elm Street, Nato			ma, KS 67651		Latitude:			
					Longitude:			
J		LL OWNER: Mr. Eldon Luhn	nan□		Elevation:			
	, St. Addr	ess, Box # :			Datum:			
City	, State, ZI	Colby, KS 6770			Data Collection			
3 LOC	CATE WE		LETED WELL .2	5	ft	•		
	CATION							
1	WITH AN "X" IN Depth(s) Groundwater Encountered (1), ft. (2), ft. (3), ft							
	SECTION BOX: WELL'S STATIC WATER LEVEL 19.03 ft. below land surface measured on mo/day/yr 5-29-08							
	N Pump test data: Well water wasft. afterhours pumpinggpm							
	Est. Yield ² gpm: Well water wasft. after hours pumpinggpm							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
W Domestic Domestic Below E Domestic Domest								
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-2								
Sample was submitted								
S								
5 TYP	E OF CAS	ING USED: 5 Wrought I	ron 8 Con	crete tile	CASIN	G JOINTS: Glued	Clamped	
	Steel	3 RMP (SR) 6 Asbestos-6	Cement 9 Othe	er (specif	v below)	Welded		
	PVC	4 ABS 7 Fiberglass				Threaded		
2 PVC 4 ABS 7 Fiberglass Threaded								
Casing height above land surface05 in., Weight 0.70 lbs./ft. Wall thickness or guage No. schedule 40								
		N OR PERFORATION MATE	RIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 0.020 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From. 15 ft. to 25 ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From 13								
From								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout In		From .0 ft. to .13	ement grout <u>D D</u>	Lamonns	ft to	A From	ft +0	
				· · · · · · · · · · · · ·	. 11. 10	ii., Fioin	II. 10II.	
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 2 Sewer lines 5 Cess pool 8 Sewage agoon 11 Fuel storage 14 Abandoned water well							16 Other (specify below)	
		sewer lines 6 Seepage pit				il well/gas well	,	
		1?				n wengas wen	***************************************	
FROM		LITHOLOGIC		FRON		PLUGGING INT		
0	4	Silt	LOG	TRON	1 10	1 LOGORNO INT	LIKVALS	
	8	Sand						
<u>4</u> 8								
	17	Clayey Silt						
17	25	Silty Clay						
				-				
			4					
				-				
			·					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year) 3-18-08								
Kansas Water Well Contractor's License No. 554/783 This Water Well Record was completed on (mo/day/year)								
under th	e business	name of Woofter Pump & Wel	II	<u> </u>	y (signature)	try [- Word to		
INSTRUC	CTIONS: U	se typewriter or ball point pen. <u>PLEAS</u> Department of Health and Environment	t Bureau of Water Cool	PRINT clea	arty. Please fill in blad	suite 420. Topo Korsas	orrect answers. Send top	
785-296-5	522. Send	l one to WATER WELL OWNE	ER and retain one	or your	records. Fee of \$5	5.00 for each constructe	d well. Visit us at	
		s.us/geo/waterwells.					, and do at	