		RECORD	Form WW	C- 5	Division of Wate	r Resources; App. No.		
1 LOCATION OF WATER WELL:			Fraction		Section Number	Township Number	Range Number	
County: Osborne			NE 1/4 NW 1/4	NW 1/4	17	T 10 S	R 15 E/W	
		ction from nearest town or cit	ty street address of	well if	-	Systems (decimal deg	rees, min. of 4 digits)	
locate	ed within cit	$^{ m y?}$ 802 N 2nd - Natoma, KS	Latitude: N39.18972					
					Longitude: W99.02322			
2 WATER WELL OWNER: NO. 1 Address Park Milan Master					Elevation: TOC 1831.76			
RR#, St. Address, Box # :					Datum:			
City, State, ZIP Code : PNatoma, KS 67651					Data Collection Method:			
	ATE WEL	L'S 4 DEPTH OF COMI	PLETED WELL.	.20	ft.			
LOCATION WITH AN "X" IN Depth(s) Groundwater Encountered (1)								
	SECTION BOX: WELL'S STATIC WATER LEVEL15.85							
SEC	N Pump test data: Well water was							
	Est. Yieldgpm: Well water wasft. after							
1		WELL WATER TO B						
	WELL WATER TO BE OSED AS. 3 Tubic water supply 8 Air conditioning 17 injection went and the conditioning 17 injection went are supply 9 Dewatering 12 Other (Specify below)							
w			ustrial 7 Dome	stic (lawn	& garden) 10 Mor	nitoring well VOBW-	1	
SV	SW SE Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs							
Sample was submitted								
	S							
5 TVDI	F OF CASI	NG USED: 5 Wrought	Iron 8 Co	ncrete tile	CASINIA	G IOINTS: Glued	Clamped	
	Steel :	RMP (SR) 6 Asbestos-	Cament 9 Ot	her (enecify	helow)	Welded	Clamped	
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped								
Blank casing diameter 4. in. to 10 ft., Diameter in. to								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From.10								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 8								
		From.	ft. t	0	ft., From	ft. to .	ft.	
		RIAL: 1 Neat cement 2						
Grout I		From Q ft. to B	,	• • • • • • • • • • • • • • • • • • • •	. ft. to 1	t., From	ft. toft.	
		source of possible contaminat		10.7.	. 1 12.7		16.04 6	
					estock pens 13 Insecticide Storage 16 Other (specify			
	Sewer lines		8 Sewago lagoon	11 Fuel s		bandoned water well	below)	
		sewer lines 6 Seepage pit				il well/gas well		
		?				DE LICONIO DI		
FROM	TO	LITHOLOGIC	CLOG	FROM	M TO	PLUGGING INT	ERVALS	
0	5	Silt	· · · · · · · · · · · · · · · · · · ·					
5	19	Fill Sand						
19	20	Silty Clay						
			····					
						· ware in the same of the same		
				•				
7 CON	TRACTO	'S OR LANDOWNER'S C	ERTIFICATION:	This water	r well was (1) const	ructed (2) reconstruc	eted, or (3) plugged	
		on and was completed on (mo						
		Contractor's License No. 554			•	// \ A . "/" - '		
under t	he business	name of Woofter Pump & W	/ell		by (signature)	tay C. Worte	q	
INSTRU	CTIONS: Us	e typewriter or ball point pen. PLE	<i>ASE PRESS FIRMLY</i> a	nd <u>PRINT</u> cle	arly. Please fill in bland	s, anderline or circle the	correct answers. Send top	
785-296-		Department of Health and Environment one to WATER WELL OWN						
		s.us/geo/waterwells.	Journ Juc	,				

KSA 82a-1212