1				WELL RECORD F	orm WWC-5	KSA 82a-			
<u> </u>	ON OF WA	rer well: Ooks Osborne	Fraction	NE 14 NW		ion Number	Township No		Range Number R 15 <b>X</b>
County:				dress of well if located	<u> </u>	) -Ja	T 10	S	R 15 AEAW
		Natoma, Kans		dress of well if located	within City?				
		D T	Pruter						
	R WELL OW	NEH. D D	1 11 11 10 1						
	Address, Bo	Matama	, Kansas	6 <b>7</b> 651				•	Division of Water Resources
City, State	, ZIP Code				Application Number:  The Elevation: Upland Upland				
J LOCATE	E WELL'S L IN SECTIO	OCATION WITH 4	DEPTH OF CO	OMPLETED WELL	٠٠٠٠خزد٠٠٠	. ft. ELEVA	LION:		
AN A	IIV SECTIO	De	epth(s) Groundv	water Encountered 1. WATER LEVEL 23	, 45	ft. 2	ي	ft. 3.	), 71 G 71 683ft.
ī [	!	ı W	ELL'S STATIC	WATER LEVEL ?.	ft. be	low land surf	face measured on	mo/day/yr	4/19/1902
	- NWX	_ NF							mping ! <i>O</i> gpm
1 [	1								mping gpm
# w  -	i	F Bo	ore Hole Diame	ter9in. to.	<u>3</u> 5	ft., ε	and	in.	to
₩ -	!	i w	ELL WATER TO	D BE USED AS: 1 5	Public water	supply	8 Air conditioning	11	njection well
ī	. – SW – –	SE	1 Domestic	3 Feedlot 6	Oil field water	er supply	9 Dewatering	12 (	Other (Specify below)
	244	35	2 Irrigation	4 Industrial 7	Lawn and g	arden only 1	0 Observation we	dl	
1 1	i	w.	as a chemical/b	acteriological sample su	ubmitted to De	partment? Ye	sNo	; If yes,	mo/day/yr sample was sub
1 -			itted			Wat	er Well Disinfecte	d? Yes <sup>X</sup>	No
5 TYPE (	OF BLANK (	CASING USED:	2	5 Wrought iron	8 Concre	te tile	CASING JOI	NTS: Glued	.X Clamped
	eel	3 RMP (SR)		6 Asbestos-Cement	9 Other (	specify below	()	Welde	ed
2 PV	/C	4 ABS		7 Fiberglass				Threa	ded
Blank casi	ing diameter	5in.	to 25	ft., Dia	in. to		ft., Dia	i	n. to ft.
Casing he	ight above l	and surface	<u>8</u>	in., weight 200		Ibs./f	t. Wall thickness	or gauge No	, •2 <del>1</del>
-	-	R PERFORATION N		7	7 PV			estos-ceme	
1 Ste	eel	3 Stainless st	teel	5 Fiberglass	8 RMI		11 Oth	er (specify)	
2 Br	ass	4 Galvanized	steel	6 Concrete tile	9 ABS			e used (op	
SCREEN	OR PERFO	RATION OPENINGS	ARE: 8	5 Gauze	d wrapped		8 Saw cut		11 None (open hole)
1 Co	ontinuous slo	ot 3 Mill s	slot		rapped	-	9 Drilled holes		
	uvered shut		punched	7 Torch	cut		10 Other (specify	n)	
		ED INTERVALS:	From 2	ft. to	35	ft Fron	n	ft. to	o
									o
(	GRAVEL PA	CK INTERVALS:	From 20	ft. to	35	ft., Fron	n	ft. to	)
			From						ft.
6 GROUT	T MATERIAI	.: 1 Neat cerr	nent :	2 Cement grout					
							ft., From	. <b>.</b>	. ft. to
		ource of possible co				10 Livest			pandoned water well
	eptic tank	4 Lateral I				11 Fuel storage		15 Oil well/Gas well	
2 Se	2 Sewer lines 5 Cess po		• •		on	12 Fertilizer storage		16 Other (specify below)	
3 W	atertight sev	ver lines 6 Seepage				13 Insecticide storage			
	from well?	g				How mar	•		
FROM	то		LITHOLOGIC I	.OG	FROM	то		LITHOLOG	IC LOG
0	4	Topsoil							
1	12	Brown clay							
12	31	White rock							
31	35	Shale							
, <u>-</u>									
		2'							
***									
1	J								1
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was									
completed on (mo/day/year) April 19, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 199 This Water Well Record was completed on (mo/day/yr) 1982 under the business name of Karst Water Well Service by (signature)									
		's License No	Wat on Ma	This Water We	ell Record was	s completed of	on (mo/day/yr)	. د ۱۰ کیفونا	+7.94
	business na	me of Marab	water, we.	TT DGT.ATCG		by (signat	ure)//6 /C	an	<b>*</b>
INSTRUC	TIONS: Use	typewriter or ball poi	int pen, <i>PLEASI</i>	ent Division of Factor	PHINT clearly	/. Please fill ir	n blanks, underline	or circle the	e correct answers. Send top Send one to WATER WELL
		ne for your records.	and Environm	OIR, DIVISION OF ENVIRON	HOIR, ENVIRONI	nemai Geolog	,, occion, ropeka	, 110 00020.	SOIN ON IO TANTER THELL