


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 26 Township Number T 10 S Range Number R 17 R/W

Distance and direction from nearest town or city street address of well if located within city?
3 miles south of Codell, Kansas

2 WATER WELL OWNER: Equitable Insurance Co.
RR#, St. Address, Box #: 889 N. Maize Rd. Suite 201 Board of Agriculture, Division of Water Resource
City, State, ZIP Code: Wichita, Kansas 67212 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 615 ft. ELEVATION: Upland
Depth(s) Groundwater Encountered 1. 528 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 300 ft. below land surface measured on mo/day/yr 6/2/93
Pump test data: Well water was 300 ft. after 1 hours pumping 20 gpm
Est. Yield 20 gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 7 7/8 in. to 615 ft., and in. to ft.
WELL WATER TO BE USED AS: 1 5 Public water supply 8 Air conditioning 11 Injection well
2 Irrigation 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 2 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded
Blank casing diameter 5 in. to 575 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 24 in., weight 3.43 lbs./ft. Wall thickness or gauge No. 327
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 575 ft. to 615 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 40 ft. to 615 ft., From ft. to ft.

6 GROUT MATERIAL: 3 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 4 ft. to 40 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination: None 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Topsoil	522	528	Very red clay
4	65	Clay, rock layers	528	532	Red clay, hard sandrock layers
65	85	Gray sandy clay	532	570	Red and white clay
85	280	Sticky shale	570	575	Very fine sandrock
280	355	Hard dry shale	575	585	Gray clay
355	395	Very hard grainy shale, white layer	585	590	Very fine sandrock
395	415	Soft Dakota clay, white layers	590	597	Red clay
415	435	Soft Dakota clay	597	615	Coarse sandrock
435	450	Hard grainy shale			
450	455	Hard shale, white rock layers			
455	490	Gray Dakota clay			
490	495	Very hard gray rock			
495	506	White Bentonite clay			
506	510	Very red clay			
510	522	Red, white, yellow clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/2/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 199 This Water Well Record was completed on (mo/day/yr) 6/23/93 under the business name of Karst Water Well Drilling & Service, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.