WATER WELL RECORD			Form WWC-5			Division of Water Resources App. No.			
1 LOCATION OF WATER WELL:			Fraction					Range Number	
County: Rooks SW 1/4 SW 1/4 NE 1/4 1/4						36	T 10 S	<u> </u>	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here									
Rooks-Ellis co. line 2 South to CC Rd, 1 E to 19 Rd, 1 south						Longitude: (in decimal degrees)			
ROOKS-EIIIS CO. IIII 2 SOULIT TO CC Nu, T E TO 19 Nu, T SOULIT						Elevation:			
2 WATER WELL OWNER: Wayne Carmicheal						Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Wayne Carmicheal RR#, Street Address, Box #: 706 SW 9th St						Collection Method:  GPS unit (Make/Model:)			
City, State, ZIP Code : Hays, Ks 67601						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Tidyo, No orosi						Est. Accuracy:			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 54									
	SECTION BOX: Depth(s) Groundwater Encountered (1).25								
	N WELL'S STATIC WATER LEVEL. 27 ft. below land surface measured on mo/day/yr. 05/09/14								
	Pump test data: Well water was .38ft. after .1 hours pumping .10 gpm								
EST. YIELD. 10gpm. Well water wasft. after									
W Bore Hole Diameter 10									
WELL WATER TO BE USED AS:   Public water supply   Geothermal   Injection well									
SWSE   Domestic   Feediot   Oil field water supply   Dewatering   Other (Specify below)									
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No									
S If yes, mo/day/yr sample was submitted									
1 mile  Water well disinfected? ✓ Yes □ No									
5 TYPE OF CASING USED: Steel V PVC Other									
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded									
Casing diameter .5									
Casing height above land surface24									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From54 ft. to20 ft., From ft. to ft.									
From									
Grout Intervals: From .20									
What is the nearest source of possible contamination:									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens									
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel stor ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer									
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well  Direction from well									
FROM	TO	LITHOLOG		FROM	TO	LITHO. LO	OG (cont.) or PLU	GGING INTERVALS	
0	3	Top Soil							
3	10	Gumbo Clay	,						
10	17	Sand & Clay	· · · · · · · · · · · · · · · · · · ·			ļ			
17	32 54	Loose limestone and sa Shale	and					,	
32	34	Snale							
				1					
		V							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   constructed, □ reconstructed, or □ plugged									
under my jurisdiction and was completed on (mo/day/year) .05/09/14 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No0199 This Water Well Record was completed on (mo/day/year) .05/16/14									
under the business name ofKarst Water Well Drilling & Service, Inc									
INSTRUC	CTIONS:	Use typewriter or ball point pen	. <u>PLEASE PRESS FIRML)</u>	and <u>PRINT</u> c	learly. Ple	ease fill in blanks	and check the correct	and create and copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html									