

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Rooks Fraction: SE 1/4 NW 1/4 NW 1/4 Section Number: 28 Township Number: T 10 S Range Number: R 18 E/W

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 South, 2 1/2 West of Plainville, Kansas

2 WATER WELL OWNER: Mary Mowry
 RR#, St. Address, Box # : R.R. Box 16
 City, State, ZIP Code : Plainville, Kansas 67663
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 160 ft. ELEVATION: Upland
 Depth(s) Groundwater Encountered 1. 70 ft. 2. 70 ft. 3. 70 ft.
 WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr May 6, 1983
 Pump test data: Well water was 150 ft. after 1 hours pumping 7 gpm
 Est. Yield 7 gpm: Well water was 160 ft. after 7 hours pumping 7 gpm
 Bore Hole Diameter 2 in. to 160 ft., and 160 in. to 160 ft.
 WELL WATER TO BE USED AS: 1 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted 7
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 2 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
 2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 70 ft., Dia 5 in. to 150 ft., Dia 160 in. to 160 ft.
 Casing height above land surface 16 in., weight 160 lbs./ft. Wall thickness or gauge No. .26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 70 ft. to 90 ft., From 150 ft. to 160 ft.
 GRAVEL PACK INTERVALS: From 150 ft. to 160 ft., From 160 ft. to 160 ft.

6 GROUT MATERIAL: 1 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 14 ft., From 15 ft. to 15 ft., From 15 ft. to 15 ft.
 What is the nearest source of possible contamination: 15
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Northwest How many feet? 3000

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	12	Brown clay			
12	70	White rock			
70	94	Clay and sand			
94	160	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 6, 1983 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 199 This Water Well Record was completed on (mo/day/yr) May 13, 1983 under the business name of Karst Water Well Service by (signature) MB Karst

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.