


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Rooks Fraction: NE 1/4 SW 1/4 SW 1/4 Section Number: 26 Township Number: T 10 S Range Number: R 19 E(1)

Distance and direction from nearest town or city street address of well if located within city?
6 miles south and 1 mile east of Zurich, Ks.

2 WATER WELL OWNER: Dan Sanchez
 RR#, St. Address, Box #: 801 S. Broadway
 City, State, ZIP Code: Plainville, Ks 67663
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 71 ft. ELEVATION: N/A
 Depth(s) Groundwater Encountered 1. 22 ft. 2. 22 ft. 3. 22 ft.
 WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on 11-6-96
 Pump test data: Well water was 55 ft. after 1 hours pumping 12 gpm
 Est. Yield 14+ gpm: Well water was 49 ft. after 2 hours pumping 12 gpm
 Bore Hole Diameter: 10 in. to 71 ft., and 71 in. to 71 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well livestock pasture
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? es No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 42 ft., Dia 5 in. to 62-72 Dia 5 in. to 62-72 Dia 5 in. to 62-72 Dia
 Casing height above land surface 24 in., weight 24 lbs./ft. Wall thickness or gauge No. 24
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 62 ft. to 42 ft., From 62 ft. to 42 ft., From 62 ft. to 42 ft., From 62 ft. to 42 ft.
 GRAVEL PACK INTERVALS: From 71 ft. to 20 ft., From 71 ft. to 20 ft., From 71 ft. to 20 ft., From 71 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 20 ft. to 0 ft., From 20 ft. to 0 ft., From 20 ft. to 0 ft., From 20 ft. to 0 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? 1/4 mile SE
 How many feet? 1/4 mile SE

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	loess			
2	6	broken yellow lms			
6	22	intermittent lms & clay			
22	46	lms fractured			
46	52	siltstone, gray			
52	61	Siltstone & lms			
61	68	Siltstone & clay			
68	71	hard shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-6-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 608 This Water Well Record was completed on (mo/day/yr) 11-15-96 under the business name of Yellow Jacket Drilling by (signature) Erin Waddell geology

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.