

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: OTTAWA	SW ¼ SW ¼ SE ¼	16	T 10 S	R 2W EW

Distance and direction from nearest town or city street address of well if located within city?
¼ MILE WEST OF INTERSECTION OXBOW RD. AND 210th. RD. NORTH SIDE

2 WATER WELL OWNER: EDWARD WRIGHT
 RR#, St. Address, Box # : 603 E. 3rd.
 City, State, ZIP Code : MINNEAPOLIS, KS. 67467
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 109 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 69 ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL 69 ft. below land surface measured on mo/day/yr 6-24-02
	Pump test data: Well water was 76 ft. after 1 hours pumping 15 gpm
	Est. Yield 40 gpm: Well water was . ft. after . hours pumping . gpm
	Bore Hole Diameter 9 in. to 109 ft., and . in. to . ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes. . No. <u>X</u> ; If yes, mo/day/yr sample was sub- mitted
	Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter 5 in. to 99 ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface 20 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26

CASING JOINTS: Glued. X Clamped.
 5 Wrought iron 8 Concrete tile
 10 Asbestos-cement

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot .025	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 99 ft. to 109 ft., From . ft. to . ft.
 From 21 ft. to 109 ft., From . ft. to . ft.

GRAVEL PACK INTERVALS: From 21 ft. to 109 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 21 ft., From . ft. to . ft., From . ft. to . ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SOUTH How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	8	SANDY LOAM			
8	11	CLAY BROWN			
11	12	CLAY RED			
12	16	CLAY GRAY			
16	109	SANDSTONE TAN			
109		SHALE GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-24-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 388 This Water Well Record was completed on (mo/day/yr) 6-24-02 under the business name of PESTINGER PUMP SERVICE by (signature) *Paul Pestinger*