WATER WELL RECORD	Form WWC-5	Division of Water R	esources App. N	o. L	
1 LOCATION OF WATER WELL County: Graham	Fraction 4 SW 4 NE 4 NW 4		ownship No.	Range Number R 23 □E ☑W	
Street/Rural Address of Well Locat					
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					
· —		Longitude: (in decimal degrees)			
115 ft from W line & 1110 ft from N line		Elevation: (in decimal degrees)			
	Detum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
2 WATER WELL OWNER: Carmen Ruder		Collection Method:			
RR#, Street Address, Box # 1176 240th Ave		GPS unit (Make/Model:)			
City, State, ZIP Code Wakeeney, KS 67672		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Est. Accuracy:					
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 70 ft					
SECTION BOX: Depth(s) Groundwater Encountered (1)					
N WEIT'S	WELL'S STATIC WATER LEVEL				
	Pump test data: Well water was				
	Dgpm. Well water was	f offer	hours pung	ping gpm	
W NW NE EST. YIEL. Bore Hole I	Diameter 8.5 in to 70	and in to	Mours puin	րուց gpin	
W Bore Hole Diameter 8.5 in. to .70 ft., and in. to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
Domestia D Foodlet D Oil field water graphy D Domestoring D Other (Specify below)					
SWSE					
Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/yr sample was submitted					
Water well disinfected? Was submitted:					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter 4.5 in to 70 ft., Diameter in to ft., Diameter in to ft.					
Casing height above land surface. 18 in., Weight 2.5 lbs./ft., Wall thickness or gauge No. 0.248					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel PVC Other (Specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From ft. to ft.					
From					
GRAVEL PACK INTERVALS: From 25 ft. to 70 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Neat cement Cement grout 2 Bentonite Other					
Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
. = . =	ral lines Pit privy Livestock	_		er (specify below)	
Sewer lines Cess Watertight sewer lines Seep	pool ☐ Sewage lagoon ☐ Fuel storag age pit ☐ Feedyard ☐ Fertilizer st				
Direction from well		6mam ====11		***************************************	
	LOGIC LOG FROM		(cont) or PLU	GGING INTERVALS	
0 2 Surface	TROM	10 11110.100	(WAIL) OL FLU	COUNT MATERIANES	
5 10 Clay 10 25 Fine sand with san	rdstone str				
	DIRE				
34 42 Clay w/ caliche		,		**************************************	
42 52 Fine sand w/ clay 8					
52 65 Sandy clay with ca	liche & a Tew				
fine sand str			,		
65 70 Brown shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged					
under my jurisdiction and was completed on (mo/day/year) 8/07/12 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 838 This Water Well Record was completed on (mo/day/sear) 8/29/12					
under the business name of D&R Pump Service, LLC by (signature)					
INSTRUCTIONS: Use ty pewriter or ball point pea. <u>PLEASE PRESS FRMLY</u> and <u>PRINT</u> clearly. Please fift in blanks and clack the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E avironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Snite 420, Topeka, Kansas 666 12-1367.					
	WATER WELL OWNER and retain one for y				
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					