


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 4 Township Number T 10 S Range Number R 24 E/W  
 County: Graham  
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Clair Legere Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box #: P. O. Box 207, Penokee, KS 67659 Application Number:  
 City, State, ZIP Code:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL 127 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 120 ft. 2. 127 ft. 3. 127 ft.  
 WELL'S STATIC WATER LEVEL 120 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 120 ft. after 127 hours pumping 127 gpm  
 Est. Yield 120 gpm: Well water was 127 ft. after 127 hours pumping 127 gpm  
 Bore Hole Diameter 8 in. to 127 ft. and 127 in. to 127 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes     No X If yes, mo/day/yr sample was sub-  
 mitted Water Well Disinfected? Yes     No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped      
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded      
 2 PVC 4 ABS 7 Fiberglass Threaded      
 Blank casing diameter 5 in. to 107 ft., Dia     in. to     ft., Dia     in. to     ft.  
 Casing height above land surface 18 in., weight 2,355 lbs./ft. Wall thickness or gauge No. 214  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)      
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)      
 SCREEN-PERFORATED INTERVALS: From 107 ft. to 127 ft., From     ft. to     ft.  
 From     ft. to     ft., From     ft. to     ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 127 ft., From     ft. to     ft.  
 From     ft. to     ft., From     ft. to     ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other      
 Grout Intervals: From 0 ft. to 20 ft., From     ft. to     ft., From     ft. to     ft.  
 What is the nearest source of possible contamination: None 10 Livestock pens 14 Abandoned water well  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	15	Loess			
15	21	Clay & Caliche			
21	23	Cemented Sand			
23	34	Sandy Clay			
34	40	Med. Sand w/Clay			
40	62	Sandy Clay & Caliche w/Sand Strks.			
62	64	Caliche-Hard			
64	76	Med. Sand w/Clay			
76	120	Sandy Clay & Caliche w/Sand Strks.			
120	126	Med. Sand w/Clay			
126	127	Ochre/Flint Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-2-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 4-14-97 under the business name of Woofter Pump & Well, Inc. by (signature) Jay C. Woofter