


1 LOCATION OF WATER WELL: County: Shawnee Fraction: SW 1/4 NE 1/4 SE 1/4 Section Number: 12 Township Number: T 10 S Range Number: R 24 EW

Distance and direction from nearest town or city street address of well if located within city?  
Eleven miles South + Two East of Panshee Kansas

2 WATER WELL OWNER: Ogwood Mays Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box #: 904 4th St Wabeneey Kansas Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 94 ft. ELEVATION:  
 Depth(s) Groundwater Encountered: 1. 74 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 74 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield: 8 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 10 in. to 94 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 Domestic  3 Feedlot  6 Oil field water supply  9 Dewatering  12 Other (Specify below)  
 2 Irrigation  4 Industrial  7 Lawn and garden only  10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel  3 RMP (SR)  6 Asbestos-Cement  9 Other (specify below)  Welded  
 2 PVC  4 ABS  7 Fiberglass  Threaded  
 Blank casing diameter: 5" in. to 74 ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface: 20 in., weight 160 lbs./ft. Wall thickness or gauge No.  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel  3 Stainless steel  5 Fiberglass  8 RMP (SR)  11 Other (specify)  
 2 Brass  4 Galvanized steel  6 Concrete tile  9 ABS  12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot  3 Mill slot  5 Gauzed wrapped  8 Saw cut  11 None (open hole)  
 2 Louvered shutter  4 Key punched  6 Wire wrapped  9 Drilled holes  
 7 Torch cut  10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 74 ft. to 94 ft., From ft. to ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 50 ft. to 94 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:  1 Neat cement  2 Cement grout  3 Bentonite  4 Other  
 Grout Intervals: From 50 ft. to 20 ft., From 20 ft. to 0 ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank  4 Lateral lines  7 Pit privy  10 Livestock pens  14 Abandoned water well  
 2 Sewer lines  5 Cess pool  8 Sewage lagoon  11 Fuel storage  15 Oil well/Gas well  
 3 Watertight sewer lines  6 Seepage pit  9 Feedyard  12 Fertilizer storage  16 Other (specify below)  
 13 Insecticide storage 200 feet  
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	Surface Clay			
15	28	Fine sand			
28	42	med sand			
42	55	Hard Grey Clay			
55	68	Hard Tan Clay			
68	79	Fine sand			
79	90	med sand			
90	94	Blue shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Oct 16-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 444 This Water Well Record was completed on (mo/day/yr) Oct 16-91 under the business name of Induson Drilling by (signature) Induson Drilling