


LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 14 Township Number T 10 S Range Number R 25 E/W

Distance and direction from nearest town or city, street address of well if located within city?
In the township of St. Patrick Kansas at the Catholic Church

WATER WELL OWNER: Robert Pfeiffer
 RR#, St. Address, Box #: Route 1 Box 21 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Marland Kansas Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 DEPTH OF COMPLETED WELL: 74 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 60 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 60 ft. below land surface measured on mo/day/yr May 15-91
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 20 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 10 in. to 74 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF CASING USED:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 Fiberglass 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 2 PVC 3 RMP (SR) 4 ABS 5 Fiberglass 6 Concrete tile 7 Fiberglass 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 Blank casing diameter: 5" in. to 54' ft., Dia. in. to ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface: 24" in., weight lbs./ft. Wall thickness or gauge No. 160 P.S.I.

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS:
 From 54' ft. to 74' ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS:
 From 74' ft. to 40 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

GROUT MATERIAL:
 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 14 Abandoned water well 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? How many feet? 15 feet

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	Surface Clays			
22	30	Hard yellow Clay			
30	36	Loam sand			
36	45	White Rock			
45	52	Fine sand			
52	60	Hard Rock			
60	74	Large sand			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 15-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 444 This Water Well Record was completed on (mo/day/yr) May 15-91 under the business name of Anderson Drilling by (signature) Paul Anderson

OFFICE USE ONLY T R EW SEC.