			WATE	R WELL RECORD Fo	orm WWC-5					
LOCATIO		ER WELL:	Fraction			tion Number	1 4	^	Range I	Number
County:		ridan		NE ¼ SW	1/4	13	<u> </u>	U S	R 2/	<u> </u>
Distance and	d direction	from nearest tow	n or city street a	ddress of well if located	within city?					, –
				·····						
WATER	WELL OW	^{NER:} Leo	Goetz							
RR#, St. Ad	ddress, Bo		1 Box 2	5			Board o	f Agriculture,	Division of Wa	ter Resources
City, State, .		<u>: Par</u>	k, Ks. 6	7751			AL . A . AL .	ion Number:		
LOCATE	WELL'S L	OCATION WITH	DEPTH OF C	OMPLETED WELL	40	ft. ELEVA	ATION:			<i></i>
AN "X" IN	N SECTIO	BOX:	ப Depth(s) Ground	water Encountered 1		ft.	2	, ft. :	3	
.	1	·	WELL'S STATIC	water Encountered 1 WATER LEVEL	25 . ft. b	elow land su	rface measured	on mo/day/yr		
1	1	i		p test data: Well water						
	- NW	NE		gpm: Well water						
1	!			eter				•		
ŧ w ├─		E1				er supply	8 Air condition		Injection well	
_								•	•	. halawi
	- SWA -	SE	1 Domestic			ter supply	•			
	1		2 Irrigation				10 Monitoring v			
 	1		Was a chemical	bacteriological sample sul	omitted to D					
<u>.</u>			mitted			·	ater Well Disinfe			X
TYPE OF	F BLANK (CASING USED:		5 Wrought iron	8 Concr			_	ed X Clam	•
1 Stee	el	3 RMP (SR	R)	6 Asbestos-Cement	9 Other	(specify belo	ow)	Weld	ded	
2 PVC		4 ABS		7 Fiberglass					aded	
•	_			20 ft., Dia						
Casing heig	ht above la	and surface	1.8	.in., weight 2	. 3.8	Ibs.	./ft. Wall thicknes	ss or gauge N	No 24	48
TYPE OF S	CREEN O	R PERFORATION	N MATERIAL:		7 PV	<u>c</u>	10 /	Asbestos-cem	ent	
1 Stee	el .	3 Stainless	steel	5 Fiberglass	8 RM	IP (SR)	11 (Other (specify)	
2 Bras	SS	4 Galvanize	ed steel	6 Concrete tile	9 AB	S	12 1	None used (o	pen hole)	
SCREEN O	R PERFO	RATION OPENING	GS ARE:	5 Gauzed	wrapped		8 Saw cut		11 None (op	en hole)
1 Con	tinuous slo	t 3 Mil	II slot	6 Wire wr	apped		9 Drilled hole	es		
2 Louv	vered shut	er 4 Ke	y punched	7 Torch c	⊔t		10 Other (spe	cify)		
		ED INTERVALS:	From	2.0 ft. to	4.0	ft Fro	om	ft.	to	
00			From	ft. to		•				
GF	RAVEL PA	CK INTERVALS:	From	15 .	40	ft Fro	om	ft.	to	
σ.		on nerelitation	From	ft. to		ft., Fro		_		ft.
GROUT	MATERIAL	: 1 Neat c		2 Cement grout	3 Bento		Other			
Grout Interv				ft., From						
		ource of possible of		NONE	11.		stock pens		Abandoned wat	
		4 Latera		-			•		Dil well/Gas we	
•	tic tank						uel storage 15 Oil well/Gas well ertilizer storage 16 Other (specify below)			
	ver lines	5 Cess	•	• •			nsecticide storage			
	•	er lines 6 Seepa	age pit	9 Feedyard			•			
Direction fro			LITHOLOGIC	100	FROM	How ma	any feet?	PLUGGING	INTERVALS	
FROM		Curfogo	LITHOLOGIC	LOG	FHOW	'0		120001110	INTERVALO	
0	2	Surface								
2	5	Loess	3 0 0							
5	8	Med. Sand								
8				Some Sand st	•					
24	30	Med. Sand		el w/a few		 			,	
			Clay S	crks.		 				
30	40	Shale			ļ	 				
				ELL MARK CARL COMPANY		ļ				
						<u> </u>				
		2000								
7 CONTO	ACTORIO :		D'S CERTIFICAT	ION: This water well was	/1\ const	oted (2) res	constructed or "	8) plugged in	der my jurisdia	tion and was
T CONTRA	ACTOR'S (JR LANDOWNEH	19_5_	ION: This water well was 9.4	(1) constru	ond this are	ord is true to the	, piuggea un	nowlodge and b	notion Kanaca
										Jellel, Nansas
water Well	Contractor	s License No. ⊋.	.⊣≇ Ar Dumo	This Water Wel	Hecord wa				^ 	<u></u>
				& Well, Inc.		by (signa		WH T	work	
INSTRUC	TIONS: Use ty	pewriter or ball point p	en. PLEASE PRESS	FIRMLY and <u>PRINT</u> clearly. Pleas 20-0001. Telephone: 913-296-554	e fill in blanks, 5. Send one to	underline or circ	le the correct answer	s. Serio top three	e copie s∕ to Kansas Is	Department
oi Health	and Environm	ioni, buidau oi water,	TOPONA, INALISAS 000	20 0001. Totaphono. 910-290-004				, , , , , , , , , , , , , , , , ,		