

"Correction"

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No. [] Well ID []

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Sheridan Fraction NE 1/4 SE 1/4 NE 1/4 SE 1/4 Section Number 7 Township Number T 10 S Range Number R 29 E W

2 WELL OWNER: Last Name: Robben First: Charles Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: 11647 S Road 80 W, Grinnell, Ks 67738

3 LOCATE WELL WITH "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the SE corner]

4 DEPTH OF COMPLETED WELL: 202 ft. Depth(s) Groundwater Encountered: 1) 120 ft. 2) ... ft. 3) ... ft., or 4) Dry Well WELL'S STATIC WATER LEVEL: 120 ft. below land surface, measured on (mo-day-yr) 10/17/2021

5 Latitude: 39.196242 (decimal degrees) Longitude: -100.59234 (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model): (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper

6 Elevation: ... ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: [X] Household [] Lawn & Garden [X] Livestock [] Irrigation [] Feedlot [] Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? [] Yes [X] No If yes, date sample was submitted: Water well disinfected? [X] Yes [] No

8 TYPE OF CASING USED: [] Steel [X] PVC [] Other CASING JOINTS: [X] Glued [] Clamped [] Welded [] Threaded Casing diameter 5 in. to 202 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in. Weight 160 lbs./ft. Wall thickness or gauge No. SDR26

TYPE OF SCREEN OR PERFORATION MATERIAL: [] Steel [] Stainless Steel [X] PVC [] Other (Specify) [] Brass [] Galvanized Steel [] None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: [X] Continuous Slot [] Mill Slot [] Gauze Wrapped [] Torch Cut [] Drilled Holes [] Other (Specify) [] Louvered Shutter [] Key Punched [] Wire Wrapped [] Saw Cut [] None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 162 ft. to 202 ft., From ... ft. to ... ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 25 ft. to 202 ft., From ... ft. to ... ft., From ... ft. to ... ft.

9 GROUT MATERIAL: [] Neat cement [] Cement grout [X] Bentonite [] Other Grout Intervals: From 0 ft. to 25 ft., From ... ft. to ... ft., From ... ft. to ... ft.

Nearest source of possible contamination: No potential source of contamination within 200 ft. [] Septic Tank [] Lateral Lines [] Pit Privy [X] Livestock Pens [] Insecticide Storage [] Sewer Lines [] Cess Pool [] Sewage Lagoon [] Fuel Storage [] Abandoned Water Well [] Watertight Sewer Lines [] Seepage Pit [] Feedyard [] Fertilizer Storage [] Oil Well/Gas Well [] Other (Specify) Direction from well? South Distance from well? 25 ft.

Table with 6 columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows show depth intervals and lithology: 0-5 Topsoil, 5-16 Yellow Dirt, 16-32 Clay, 32-64 Sandy Clay, 64-80 Clay, 80-96 Fine Sand/Clay Streaks, 96-112 Fine Sand, 112-120 Clay, 120-128 Med. Gravel. Notes: Minimum distance approved by NWKLEPG out of Colby, KS

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was [X] constructed, [] reconstructed, or [] plugged under my jurisdiction and was completed on (mo-day-year) 10/22/2021 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 376 This Water Well Record was completed on (mo-day-year) 10/27/2021 under the business name of B. & B. Drilling