	WELL REC		Form W	WC-5	Di		r Resources App. N		
	OCATION OF WATER WELL: ounty: Ottawa		Fraction SW ¼ NE ¼ SW	/ ¼ SW ¼		on Number 21	Township No. T 10 S	Range Number R 03 □E ☑W	
Street/R	Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:			
1	from nearest town or intersection: If at owner's address, check he Intersection of Nugget Road and N-140th Road go north 1/2					Latitude: .39.16441 (in decimal degrees) Longitude: -97.66508 (in decimal degrees)			
	site on the west of road					Elevation: 1320.18			
1	Ollawa Coulity					ction Method:			
RR#, Street Address, Box #: 307 N Concord City, State, ZIP Code : Minneapolis KS 67467					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
		· Minnear	olis, KS 67467		Est. A	ccuracy: $\square$	3 m, 3-5 m,	5-15 m, $\square$ >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 16									
SECTIO	SECTION BOX: Depth(s) Groundwater Encountered (1).14.5 ft. (2)								
	<del>``                                   </del>	Pump test data: Well water was. N/Aft. after. N/A hours pumping. N/A gpm							
NW	NE	EST. YIELD. N/Agpm. Well water was. N/Aft. after. N/A hours pumping. N/A gpm							
w L	E	Bore Hole Diameter 6							
sw	- SE	☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)							
Domestic Feedlot Oil field water supply Dewatering Other (Specify be Irrigation Industrial Domestic-lawn & garden Monitoring well									
	S If yes, mo/day/yr sample was submitted								
Water well disinfected? ☐ Yes ☑ No									
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other									
Casing diameter .2 in. to .11 ft., Diameter in. to ft., Diameter ft.									
Casing height above land surface30									
☐ Steel ☐ Stainless Steel ☐ VC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)									
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)									
From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS:       From									
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other									
Grout Intervals: From 7									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)									
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well VOC's									
Direction from well N/A Distance from well N/A									
FROM 10	TO Clay	LITHOLOGI	C LOG	FROM	TO	LITHO, LO	OG (cont.) or PLU	IGGING INTERVALS	
10 16	Fine Sa								
16 20	Sandy C	Clay							
							14		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .26-13 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 597 This Water Well Record was completed on (mo/day/year) 3-20-13 under the business name of Boart Longyear									
INSTRUCTIO	ONS: Use typewri	iter or ball point pen.	PLEASE PRESS FIRMLY	and PRINT cle	early. Ple	ase fill in blanks	and check the correct	t answers. Send three copies	
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.  KSA 82a-1212  Check: White Copy, Blue Copy, Pink Copy									
		6	MW 1207			<u> </u>	177	- F777	

KSA 82a-1212