			WWC-5		Division of			W 11 II			
			ge in Well Use		esources A		T	Well ID	as Number		
1 LOCATION OF WATER WELL: County: Sheridan			Fraction SE 1/4 SE 1/4 SE 1/4) . I			Township Numbe		ge Number		
			4 T 10 S R 30 DE W ural Address where well is located (if unknown, distance and								
					direction from nearest town or intersection): If at owner's address, check here:						
Address: 12008 W Road 110 S					•						
- K					1 North, 1 East Of Angelus, Ks						
City: Grinnell State: Ks ZIP: 67738											
3 LOCAT		4 DEPTH OF CON									
	WITH "X" IN SECTION BOX: Depth(s) Groundwater Encountered: 1)1.1										
N			3) ft., or 4) [☐ Dry Well		Horizontal Datum: ☐ WGS 84 ☐ NAD 83 ☐ NAD 27					
WELL'S STATIC WATE			TER LEVEL:1.			Source for Latitude/Longitude:					
						☐ GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No)					
				ater was ft.			Land Survey Topographic Map				
w after hours pumpi											
Well wat			water was	ft.							
1 and the state of			pumping gpm			6 Elevation:ft. ☐ Ground Level ☐ TOC					
Estimated Yield: 30 Bore Hole Diameter:			/gpm 4 in to 174					GPS Topographic Map			
Bole Hole Diameter				ft Other							
7 WELL WATER TO BE USED AS:											
1. Domestic			ater Supply: well ID		10.	Oil Fi	eld Water Supply: le	ase			
☐ House	☐ Household 6. ☐ Dewatering: how many wells?				11.	11. Test Hole: well ID					
1	■ Lawn & Garden 7. ☐ Aquifer Recharge: well ID										
ı —	☐ Livestock 8. ☐ Monitoring: well ID						nal: how many bores				
2.					•••	a) Closed Loop ☐ Horizontal ☐ Vertical b) Open Loop ☐ Surface Discharge ☐ Inj. of Water					
3. ☐ Feedlo 4. ☐ Industr		☐ Recovery		Extraction	13.						
4. ☐ Industrial ☐ Recovery ☐ Injection 13. ☐ Other (specify):											
Water well disinfected? Yes No											
8 TYPE OF CASING USED: Steel PVC Other											
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.											
Casing height above land surface 12 in. Weight 250 lbs./ft. Wall thickness or gauge No. 250											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)											
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:											
SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)											
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)											
SCREEN-PERFORATED INTERVALS: From											
GRAVEL PACK INTERVALS: From 100 ft. to 174 ft., From ft. to ft., From ft. to ft.											
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other											
Grout Intervals: From											
Nearest source of possible contamination: Septic Tank											
Sewer		☐ Cess Pool			☐ Fuel St		☐ Abando				
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well											
☐ Other (Specify)											
							THO. LOG (cont.) or	DLUCCIN	CINTERVALS		
10 FROM 0	TO 5	LITHOLO	GIC LOG	FROM	10) LI	HO. LOG (cont.) or	PLUGGIN	JINTERVALS		
5	64	Topsoil Clay									
64	90	Sandy Clay									
90	112	Gravel									
112	125	Gravel Sandy Clay									
125	150	Clay S Stone									
150	160	Gravel		Notes:							
160	170	Sandstorie									
170 174 Ochra											
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged											
under my jurisdiction and was completed on (mo-day-year) .8-17											
under the business name of B.& B. Drilling LLC. Signature Signature Signature											
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,											
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.											
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015									7/10/2015		