


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: THOMAS		SE 1/4 NE 1/4 NW 1/4	5	T 10 S S	R 31 W E (W)
Distance and direction from nearest town or city street address of well if located within city? 6 N 460 East of Oakley					
2 WATER WELL OWNER:		MR. JOSEPH STRABALA			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		COLORADO SPRINGS, COLORADO		Application Number: T-88-14	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 160 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 90 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 58 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 50 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 160 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
7 Fiberglass		Welded			
		Threaded			
Blank casing diameter 5 in. to 150 Dia 150 in. to ft. Dia in. to ft.					
Casing height above land surface 12 in. weight 250 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 150 ft. to 160 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 90 ft. to 160 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					

6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well? North		How many feet? 1000	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	21	Topsoil			
21	34	M. Gravel			
34	51	Sandy Clay			
51	72	M. Gravel			
72	80	Sandy Clay			
80	96	M. Gravel			
96	103	Sandy Clay			
103	128	M. Gravel			
128	136	Gravel			
136	148	Sandy Clay			
148	150	Sandy Clay			
150	159	M. Gravel			
159	160	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-88 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 376	This Water Well Record was completed on (mo/day/yr) 5-88
under the business name of B & T DRILLING	by (signature) Joseph Strabala
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.	