

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.


OAKLEY 1E

WATER WELL RECORD
KSA 82a-1201-1215

DLB

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County <u>Thomas</u>	Township name <u>10 NW</u>	Fraction <u>W E</u>	Section number <u>7</u>	Town number <u>10 S</u>	Range number <u>31 W</u>
Distance and direction from nearest town or city: <u>4 N 3 E of OAKLEY</u>				3 Owner of well: <u>AL SWART</u>		
Street address of well location if in city:				Address: <u>OAKLEY</u>		
Locate with "X" in section below:		Sketch map:		4 Well depth: <u>178</u> ft. Date of completion <u>1-13-75</u> Well diameter <u>28</u> in.		
				5 ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☒ Reverse rotary		
2		Type and color of material		From	To	6 Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well
		Medium Sand (Brown)		84	94	7 Casing: Material <u>Steel</u> Height: above/below Threaded ☐ Welded ☒ Surface ☐ in. Diam. <u>12 3/4</u> in. to <u>100</u> ft. depth Weight ☐ lbs./ft. ☐ No Drive shoe? ☐ Yes ☒ No
		Sandy clay + fine Sand (Brown)		94	102	8 Screen: Manufacturer <u>Slott</u> Dia. <u>12 3/4</u> Type <u>Slott</u> Slot/gauze <u>12 3/4</u> Length <u>100</u> Set between <u>100</u> ft. and <u>100</u> ft. Fittings: Gravel pack ☒ Yes ☐ No Size range of material <u> </u>
		Medium Sand (Brown)		102	110	9 Static water level: <u>109</u> ft. below land surface Date <u> </u>
		Fine Sand + Sandy clay (Brown)		110	120	10 Pumping level below land surfaces: <u>117</u> ft. after <u>3</u> hrs. pumping <u>550</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>600</u> g.p.m.
		Medium Gravel (Brown)		120	131	11 Water sample submitted: ☐ Yes ☒ No Date <u> </u>
		Sandy clay + trace Sandstone		131	136	12 Well head completion: ☐ Pitless adapter <u>12</u> inches above grade
		Sand stone (white)		136	137	13 Well grouted? ☐ Yes ☒ No ☐ Neat cement ☐ Bentonite ☐ <u> </u> Depth: From <u> </u> ft. to <u> </u> ft.
		Sandy clay + sandstone		137	142	14 Nearest source of possible contamination: ft. <u>3900</u> Direction <u>E 95 W</u> Type <u>Sewer</u> Well disinfected upon completion? ☐ Yes ☒ No
		Medium Sand (Brown)		142	153	15 Pump: ☐ Not installed Manufacturer's name <u>Gould</u> Model number <u> </u> HP <u>50</u> Volts <u>440</u> Length of drop pipe <u>170</u> ft. capacity <u>600</u> g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other
		Sand stone (white)		153	155	17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Red Tiger Irrigation</u> <u>125</u> Business name <u>Colby, Ks 1304524</u> License No. <u> </u> Address <u> </u> Signed <u> </u> Date <u>5-29-75</u> Authorized representative
		Medium Sand + Sand stone		155	173	
		O chie + shals (yellow + blue)		173	177	
		BROOK 173'				
		(use a second sheet if needed)				
16 Remarks: elevation <u>3025 (TOPO)</u>						
Topography: ☐ Hill ☒ Slope ☐ Upland ☐ Valley						