

LOCATION OF WATER WELL:		FRACTION: C 1/4 NW 1/4 NW 1/4		SECTION NUMBER: 9		TOWNSHIP NUMBER: T 10 S		RANGE NUMBER: R 31 E/W	
COUNTY: THOMAS									
DISTANCE AND DIRECTION FROM NEAREST TOWN OR CITY STREET ADDRESS OF WELL IF LOCATED WITHIN CITY?									
WATER WELL OWNER: Red Tiger Drly Co. Right #10		BOARD OF AGRICULTURE, DIVISION OF WATER RESOURCES							
RR#, ST. ADDRESS, BOX #: 1720 KANSAS STATE BANK Bldg.		APPLICATION NUMBER: T84-871							
CITY, STATE, ZIP CODE: Wichita KS, 67202									
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 168' ft. ELEVATION: 3030 GR.							
		Depth(s) Groundwater Encountered 1. 100' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 100' ft. below land surface measured on mo/day/yr 11-16-84 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 20 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8" in. to 168' ft. and in. to ft.							
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded Threaded							
Blank casing diameter 5 1/2 in. to 168' ft. Dia. in. to ft. Dia. in. to ft.									
Casing height above land surface 34" in. weight lbs./ft. Wall thickness or gauge No. 14"									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 120' ft. to 168' ft. From ft. to ft. From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 130' ft. to 168' ft. From ft. to ft. From ft. to ft. From ft. to ft.							
GROUT MATERIAL:		4 Other NONE							
Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage							
Direction from well? SW		How many feet? 100'							
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG							
0 100 Clay									
100 168 Sand									
Plugged w/ Neat Cement									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-27-84 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 11-27-84									
under the business name of Red Tiger Drly Co. by (signature) Bruce Tichel									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									