

1 LOCATION OF WATER WELL: County: Thomas		Fraction NW 1/4 SE 1/4 SW 1/4	Section Number 14	Township Number T 10 S	Range Number R 31 EW
Distance and direction from nearest town or city street address of well if located within city? 12 miles south & 1 1/2 miles west of Menlo, Ks.					
2 WATER WELL OWNER: Shea 1-14		Murfin Drilling		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box # : City, State, ZIP Code :		Box 661 Colby, Ks. 67701		Application Number: 900059	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL..... 150 ft. ELEVATION:			
<div style="text-align: center;">N +-----+ NW NE +-----+ W +-----+ E SW SE +-----+ S</div> <div style="position: absolute; left: -40px; top: 50%; transform: translateY(-50%);">1 Mile</div>		Depth(s) Groundwater Encountered 1.....ft. 2.....ft. 3.....ft.			
		WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter... 8in. to 150ft., and.....in. toft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes.....No.....					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . <input checked="" type="checkbox"/> . Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter . 4 1/2in. toft., Diain. toft., Diain. toft.					
Casing height above land surface. -36in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From.....ft. toft., From.....ft. toft.					
From.....ft. toft., From.....ft. toft.					
GRAVEL PACK INTERVALS: From.....ft. toft., From.....ft. toft.					
From.....ft. toft., From.....ft. toft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From..... 6ft. to 3ft., From.....ft. toft., From.....ft. toft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? NE				How many feet? 100	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			150	50	Washed sand
			50	6	Clay
			6	3	Cement
			3	0	Top soil
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-27-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 2-28-90 under the business name of WOOFER PUMP & WELL by (signature) <i>Walter Woofter</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					