

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: THOMAS		SE 1/4 NW 1/4 NE 1/4	23	T 10 S S	R 31 W EW
Distance and direction from nearest town or city street address of well if located within city? <div style="text-align: center; font-size: 1.2em;">3 N 1/2 W of Campus</div>					
2 WATER WELL OWNER: SLAWSON OIL CO. RR#, St. Address, Box #: 200 DOUGLAS BLDG. City, State, ZIP Code: WICHITA, KANSAS 67202 Board of Agriculture, Division of Water Resources Application Number: 786-369					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 175 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 105 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 10.5 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 30 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 175 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
		5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 165 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 12 in. weight 250 lbs./ft. Wall thickness or gauge No. 250			
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
		SCREEN-PERFORATED INTERVALS: From 165 ft. to 175 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 105 ft. to 175 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Flatland Natural Drain How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	18	Topsoil			
18	32	M. Gravel			
32	54	Sandy Clay			
54	71	M. Gravel			
71	88	Sandy Clay			
88	98	Fine Sand			
98	100	M. Gravel			
100	106	Sandy Clay			
106	116	M. Gravel			
116	151	Sandy Clay			
151	156	Fine Sand			
156	165	Sandy Clay			
165	170	M. Gravel			
170	175	Ochre			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-3-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 376 This Water Well Record was completed on (mo/day/yr) 5-87 under the business name of B & B DRILLING by (signature) Joseph Beckman					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4