

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Thomas		NE 1/4 SW 1/4 SW 1/4		31		T 10 S		R 31 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 miles east & 1 1/2 miles south of Oakley, Ks.									
2 WATER WELL OWNER: Moorehous #8 Murfin Drilling									
RR#, St. Address, Box #				Box 661			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code				Colby, Ks. 6701			Application Number: 900483		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 215 ft. ELEVATION:					
				Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
				WELL'S STATIC WATER LEVEL 120 ft. below land surface measured on mo/day/yr					
				Pump test data: Well water was ft. after hours pumping gpm					
				Est. Yield gpm: Well water was ft. after hours pumping gpm					
				Bore Hole Diameter 8 in. to 215 ft., and in. to ft.					
WELL WATER TO BE USED AS:									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)									
Was a chemical/bacteriological sample submitted to Department? Yes.....No.. x; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No x									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued .. x .. Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded									
Blank casing diameter 4.5 in. to 175 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thickness or gauge No. 248									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 <u>PVC</u> 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 6 ft. to 3 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
				215	50	Washed sand			
				50	6	Clay			
				6	3	Bentonite			
				3	0	Top surface			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) under the business name of Woofter Pump & Well by (signature)									