		WATER	WELL RECORD	Form WWC-5		2a-1212			
1 LOCATION OF WATE	R WELL:	Fraction			tion Numbe			Range Number	
County: Thomas	3	NE 1/4		NE 1/4	30	<u> </u>	0 s	R 32 E/W	
Distance and direction f 6 miles	rom nearest town o 3 North, 3				th of	Oakley			
2 WATER WELL OWN	ER: Glen C	Close	Aberc	rombie D	rillin	a. Inc			
RR#, St. Address, Box			150 M	ain Suit	- 801	Board of	Agriculture,	Division of Water Resources	
City, State, ZIP Code	Oaklev	Ks. 67	748 Wichi	ta. Ks	67202 <b>-</b>	1393 Applicati	on Number:	950227	
LOCATE WELL'S LO	CATION WITH 4	DEPTH OF CO	MPLETED WELL	1.80	ft. ELEV	/ATION:			
AN "X" IN SECTION	BOX: De	epth(s) Groundwa	ater Encountered	1	ft	. 2	ft. 3	3	
<b>†</b>   i	;     \						- •	umping gpm	
NW -	X, Es	t. Yield	gpm: Well wa	ater was	ft.	after	hours pu	umping gpm	
÷ w								ı. to	
₹ "   !	!   WE	ELL WATER TO	BE USED AS:			8 Air conditioni	•	Injection well	
ī   sw .	- SE	1 Domestic	3 Feedlot					Injection well Other (Specify below)	
		2 Irrigation	4 Industrial						
	Wa	as a chemical/ba	cteriological sampl	e submitted to Do	epartment?	YesNo	X; If yes	, mo/day/yr sample was sub-	
<u> </u>		tted			<u> </u>	Vater Well Disinfed	ted? Yes	No X d Clamped	
5 TYPE OF BLANK CA	ASING USED:	!	5 Wrought iron	8 Concre	ete tile	CASING J	OINTS: Glue	d Clamped	
1 Steel	3 RMP (SR)		6 Asbestos-Cemer	nt 9 Other	(specify bel	low)	Weld	led	
2 PVC	4 ABS		7 Fiberglass					aded	
<del>-</del>								in. to ft.	
Casing height above lar	id surface <del></del> 3.6	ir	n., weight		Ibs	s./ft. Wall thicknes	s or gauge N	lo	
TYPE OF SCREEN OR PERFORATION MATERIAL:				7 PV	С	10 A	10 Asbestos-cement		
1 Steel	1 Steel 3 Stainless steel			8 RM	P (SR)	11 C	11 Other (specify)		
2 Brass 4 Galvanized steel			6 Concrete tile	9 AB	S	11 Other (specify)			
SCREEN OR PERFORA	ATION OPENINGS	ARE:	5 Gauzed wrapped		8 Saw cut 11 None (open hole)		11 None (open hole)		
1 Continuous slot	3 Mill s	slot	6 Wire wrapped			9 Drilled holes			
2 Louvered shutte	r 4 Key p	punched	7 Tor	ch cut		10 Other (spec	ify)		
SCREEN-PERFORATE	INTERVALS:	From	ft. to		ft., Fr	rom	ft. 1	toft.	
		From	ft. to		ft., Fi	rom	ft. 1	toft.	
GRAVEL PAC	K INTERVALS:	_						toft.	
<b>1</b>									
6 GROUT MATERIAL:			Cement grout						
			ft., From	<b>n</b> .				ft. to	
What is the nearest source of possible contamination							estock pens 14 Abandoned water well		
•			7 Pit privy					Dil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage la	agoon			16 C	Other (specify below)	
<u>-</u>	r lines 6 Seepage	e pit	9 Feedyard			ecticide storage			
Direction from well?		LITUOLOGIO L	20			nany feet?	DI LICCINO 1	INITED VALO	
FROM TO		LITHOLOGIC LO	JG	FROM	TO	1	PLUGGING I	INTERVALS	
	Control (MICE)			180	102	Washed S	Sand		
				102	6	Clay			
	ws			6	3	Bentonit	:e		
				3	0	Topsoil			
					v-r	-			
						<b></b>			
			A THE MANY STREET AND THE STREET						
7 CONTRACTOR'S O	R LANDOWNER'S	CERTIFICATIO	N: This water well	was (1) constru	cted. (2) re	constructed, or (3)	plugged und	der my jurisdiction and was	
								owledge and belief. Kansas	
Water Well Contractor's									
under the business nam			ımp & Well					Worth	
								copies to Kansas Department	
of Health and Environmen									