


2411117 MW-1		WATER WELL RECORD Form WWC-5 KSA 82a-1212			
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Thomas		SW 1/4 SW 1/4 NW 1/4	14	T 10 S	R 32 EW
Distance and direction from nearest town or city street address of well if located within city? Hwy 83 & I-70; Oakley					
2 WATER WELL OWNER: John E Jones Trust #1 dba W-J oil Co.					
RR#, St. Address, Box #: 1016 S. Cedar					
City, State, ZIP Code: Stockton, KS 67669					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 3032.90 TOC			
		Depth(s) Groundwater Encountered 1. 78 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 78.03 ft. below land surface measured on mo/day/yr 12-3-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 12 in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded Flush					
Blank casing diameter 4 in. to ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface flush in. weight 703 lbs./ft. Wall thickness or gauge No. Sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 65 ft. to 95 ft. From ft. to ft.					
From 61.5 ft. to 95 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 61.5 ft. to 95 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 58 ft. From 58 ft. to 61.5 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? SE How many feet? ~200					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		2.5		Top soil / fill	
2.5		32		Silt	
32		38		Clay	
38		43.5		Sandy Clay	
43.5		44.5		Sand	
44.5		46.5		Clay	
46.5		47.5		Sand	
47.5		49		Clay	
49		64		Gravel	
64		71		Clay	
71		79		Sand	
79		84.5		Clay	
84.5		95		Ogallala	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-3-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 1-2-97 under the business name of GST by (signature) Allison M. Jones					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					