

1) LOCATION OF WATER WELL: County: Thomas Fraction: SW 1/4 SW 1/4 NW 1/4 Section Number: 14 Township Number: T 10 S Range Number: R 32 E/W

Distance and direction from nearest town or city street address of well if located within city? 1-70 W Hwy 83 (1-70 Exit 70) Oakley

2) WATER WELL OWNER: J-J Oil Co. R#2 City, State, ZIP Code: Oakley, KS 67748 Board of Agriculture, Division of Water Resources Application Number: MN7

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Section Box Diagram with X in NW corner]

4) DEPTH OF COMPLETED WELL: 93 ft. ELEVATION: 75.79 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 75.79 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 8 in. to 93 ft. and 93 ft. after hours pumping gpm

Est. Yield gpm: Well water was 93 ft. after hours pumping gpm

Bore Hole Diameter: 8 in. to 93 ft. and 93 ft. in. to 93 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X

Blank casing diameter: 2 in. to 63 ft. Dia 0 in. to 716 in. Dia 1.54 in. Dia

Casing height above land surface: 0 in. weight 716 lbs./ft. Wall thickness or gauge No. 1.54

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 63 ft. to 93 ft. From 63 ft. to 93 ft. From 63 ft. to 93 ft. From 63 ft. to 93 ft.

GRAVEL PACK INTERVALS: From 61 ft. to 93 ft. From 61 ft. to 93 ft. From 61 ft. to 93 ft. From 61 ft. to 93 ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 59 ft. From 59 ft. to 61 ft. From 61 ft. to 61 ft. From 61 ft. to 61 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Contaminated site

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 6 cement

6 5 Backfill of DK Gray Clay

5 25 Loess

25 30 Clayey Sand some gravel

30 40 gray-red sandy clay

40 50 sandy clay

50 55 Loose sand & gravel

55 60 clayey sand w/ sandy clay

60 80 Loose sand & gravel

80 95 mixed sand & gravel

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-11-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 1-22-98 under the business name of Woofler Pump & Well, Inc. by (signature) Jay C. Woofler

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.