## corrected

	WATER WELL RECORD Form WWC-5		Division of Water			Wall ID	
Original Record	Correction			irces App. No.	Tourship Mussl	Well ID er Range Number	
1 LOCATION OF WATER WELL: Fraction			Sect Sect				
direction from peacest town or intersection). If at owner's address check here:							
Address: 3602	rst	inection from it	1/4 m. le North of Oahley &				
Address:			14 11	,,,,		71/2	
City: DAKle of	State: /	53 ZIP 42748					
3 LOCATE WELL 2	4 DEPTH OF C	COMPLETED WELL:	230 ft.	5 Latitude	à.	(decimal degrees)	
WITH "X" IN SECTION BOX:	Depth(s) Groundwa	ater Encountered: 1)	. O ft.	ft. Longitude:(decimal degrees)			
SECTION BOX:	2) ft	Dry Well	Horizontal Datum: ☐ WGS 84 ☐ NAD 83 ☐ NAD 27				
		WATER LEVEL:		Source for Latitude/Longitude:			
1, 1 1 1	below land surface, measured on (mo-day-yr above land surface, measured on (mo-day-yr						
NW NE	Pump test data: W		☐ Land Survey ☐ Topographic Map				
W E	afterh		Online Mapper:				
	Well water was ft.						
SWSE	after l	nours pumping	gpm	6 Flavotio		Ground Level G TOC	
	Estimated Yield:		6 Elevation:ft. ☐ Ground Level ☐ TOC Source: ☐ Land Survey ☐ GPS ☐ Topographic Map				
S	Bore Hole Diamete	er:9 in to 230	. ft. and				
1 mile  in. to ft.							
1. Domestic:		c Water Supply: well ID		10. □ Oil F	ield Water Supply: 1	ease	
Household		tering: how many wells?					
Lawn & Garden							
☐ Livestock				. 12. Geothermal: how many bores?			
2.  Irrigation							
	3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor Extr				b) Open Loop Surface Discharge Inj. of Water		
4. Industrial Recovery Injection 13. Other (specify):							
Was a chemical/bacteriological sample submitted to KDHE?  Yes No If yes, date sample was submitted:							
Water well disinfected? ■ Yes No							
8 TYPE OF CASING USED: Steel X PVC Other							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ Fiberglass							
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☑ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)							
Louvered Shutter							
GRAVEL PACK INTERVALS: From 160 ft. to 250 ft., From 20 ft. to 160 ft., From ft. to ft.							
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Other							
Grout Intervals: From ft. to ft., From ft. to ft. to ft.							
Nearest source of possible contamination:							
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage							
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well							
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well							
☐ Other (Specify) Direction from well? 50474 Distance from well? 500 ft.							
10 FROM TO		DLOGIC LOG	FROM	TO L		r PLUGGING INTERVALS	
0 25	Class	DO GIO DOG	11.0				
25 70	Sande Class	/					
70 80	Gravel						
80 102	m Showe						
102 144	5 Eday y	revel Streets					
144 174	Sandy cl	ay			Civiainal D.		
174 228	Fine 5 on	m Grave	Notes:			eturned to Sender	
228 230 Shale for Correction Date: 5/19/							
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Aconstructed, or plugged							
under my jurisdiction and was completed on (mo-day-year)							
under the husiness name of farther war Bth Dulby 12 Signature based Beckness							
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,							
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water				ater Well Owner and retain one for your records. Telephone 785-296-5524.			
Visit us at http://www.kdhek	s.gov/waterwell/index.h	tml	KSA 82a-12	12		Revised 7/10/2015	