USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY. CAKLEY AND

WATER WELL RECORD KSA 820-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Location of well: | County | Fraction | | Section number | | Township number | Range number | |
|---|-----------------|---------------------|--|--|--|---|--------------------|----------------------------|
| | Thomas, | NW 1/45W 1/4 NW 1/4 | | 4 | | T 10 S | R 32 E | 2 |
| 2. Distance and direction from nearest town or city: 2. Owner of well: RAPPS INC, | | | | | | | | Π |
| Street orderess of well location if in city. | | | | | 4// 3. /*** | | | |
| | | | | | | 8 R. 4 h for Colo, \$0601 | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia in. Well depth ft. | | -72 |
| | | | | | | 7 Cable tool ∠Rotary | | ᅱ |
| J NW - I - NIE - I | | | | | | Hollow rodJettedBoredReverse rotary | | |
| X NW NE | | | | | ı | 8. Use: X Domestic Public supply Industry | | |
| ₩ | | | | | | Irrigation Air conditioning Stock | | |
| | | | | | | Lawn Oil field water Other | | |
| | | | | | | 9. Casing: Material Height: Above or below | | |
| | | | | | | Threaded Welded Surface in. RMP PVC Weight lbs./ft. | | |
| | | | | | | Dia. O in. to 112 ft. depth Wall Thickness: inches or | | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. dept | h gage No. 200 | _ |
| | | | | <u> </u> | | 10. Screen: Manufacturer's n | | - |
| ton suil | | | | 0 | 33 | Type PUC | | - |
| | | | | 33 | , | Slot/gauze 1/3 2 | Length | _ |
| gram | | | | 122 | 57 | Set betweenft. a | | ft. |
| sandy clay | | | | 51 | 68 | Gravel pack? Size ran | | |
| m. a a s | | | | 68 | 23 | 11. Static water level: | mo./day/y | |
| 7000 | | | | 23 | 100 | 12. Pumping level below land | | 4 |
| sandy clay & S.S. | | | | 1// | 100 | ft. after h | nrs. pumping g.p.n | |
| araul | | | | 100 | 115 | ft. after hrs. pumping g.p.m. | | |
| | | | | 115 | 112 | Estimated maximum yield 13. Water sample submitted: | mo./day/y | _ |
| Cena, | | | | 1775 | <i>" '</i> | ٠ ١٠٠ | Date | |
| 3ROCK 115" | | | | | | 14. Well head completion: | | |
| | | | | | | X Pitless adapter 12" Inches above grade | | |
| | | | | | | 15. Well grouted? X MN C Concrete | | |
| | | | | | | Depth: From 4 ft. to 4 ft. | | |
| | | | | | | 16. Nearest source of possible | | $\neg \cup$ |
| | | | | | | ft Direction Type Well disinfected upon completion? Yes No | | |
| | | | | _ | | | | <u>∾</u> (, , |
| | | | | | | 17. Pump: Manufacturer's name | ∠X Not installed |] _~ W |
| | | | | † | | | HP Volts | コル |
| | | | | | \sqcup | Length of drop pipe | ft. capacityg.p.m | ₁. (ବ) ™ |
| | | | | | | Type: Submersible | Turbine | |
| | | | | 1 | | Jet | Reciprocating | |
| | (Use a second s | heet if needed) | | | | Centrifugal | Other | ۲، ا |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's o | | J. 1 |
| 2108 MOHA | | | | | This well was drilled under my is true to the best of my know | , , | 1 | |
| Topography: | | | | | | STRUCKHOFF | SONS 298 | <u> </u> |
| — Hill | | | | | | Business name | License N | |
| Slope Upland | | | | | | Address // Od | 160 1-0 | |
| Valley Signed Authorized representative | | | | | | | | -]\$ & |
| | | | | | | | | - '2' |