USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 820-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

Job #16-77-B-35-10-32			Topeka, Nansas 00020
County Fraction	Sectio	number	Township number Range number
Thomas SW 1/4 NE 1/4 NW 1/	4 3	5	T 10 S R 32 XE/W
, IIOm ouricy;	Owner of we	II: Me	eds Redi-Mix - Dave Meeds
3/4 North; ½ East Street address of well location if in city:  R.R. or street:			
City, state, zip code: Oakley, Kansas			
4. Locate with "X" in section below:  Sketch map:			6. Bore hole dia. 30 in. Completion date 3-2-77 Well depth 155 ft.
			7 Cable tool Rotary Driven Dug
			Hollow rod Jetted Bored XReverse rotary
			8. Use: Domestic Public supply Industry
			X Irrigation Air conditioning Stock
SW SE			LawnOil field waterOther 9. Casing: Material Steel Height: Above okukuk
			Threaded Welded _XISurfacein.
S			RMPPVCWeight188 lbs./ft.
1 Mile ————————————————————————————————————		Τ.	Dia. 16 in. to 65 ft. depth Wall Thickness; inches or Dia. — in. to — ft. depth gage No. #7
5. Type and color of material	From	То	10. Screen: Manufacturer's name
	0	10	Brown Type Regular Dig. 16"
Clay			Slat/aman 10%   10%
Gravel	10	96	Set between 65 ft. and 145 ft.
6100	96	100	10 Cook 145 ft. and 155 ft. Grayel pack? X Size range of material 30% #1 70% 4x5/
Clay			33.50.00
Coarse Sand, Clay, Sandstone Streaks	100	120	11. Static water level:
Clay, Coarse Sand Streaks	120	132	12. Pumping level below land surfaces:
Clay, Coarse Band Bereaks		1	140ft. after 2 hrs. pumping 1004g.p.m.
Coarse Sand, Clay	132	140	ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.
Coarse Sand, Med. Gravel	140	145	
	145	155	Yes X No Date
Ochre, Shale		133	14. Well head completion: Pitless adapter 12 Inches above grade
19 195 195 195 195 195 195 195 195 195 1			15. Well grouted? X Clay
,			With: Neat cement X Bentonite X Concrete
			Depth: From 0 ft. to 10 ft.
			16. Negrest source of possible contamination: ft. 1300 Direction N Type Farmstead
			Well disinfected upon completion? YesX No
			17. Pump: Not installed
		-	Manufacturer's name Floway  Model number 85143 HP 40 Volts   90
			Length of drop pipe 149 ft. capacity 700 g.p.m.
			Type: 4Stage 10 DOH
		<del> </del>	Submersible X Turbine Reciprocating
(Use a second sheet if needed)			Centrifugal Other
18. Elevation: 19. Remarks:			20. Water well contractor's certification:
			This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Topography:			Western Well & Pump 245
Hill			Business name Roy 852 Collby KS 6/701 - 12
X Upland			Ally Borring Alazha
Valley			Authorized representative Date