WATE	ER WE	LL RECORD	Form W	/WC-5	Ε	Division of Wate	er Resources App. N	0		
	LOCATION OF WATER WELL:		Fraction	·	Sect	ion Number		Range Number		
	County: Sherman		SE 1/4 SW 1/4 SE	1/4 1/	4	12	T 10 S	R 40 DE VIW		
Stre	et/Rural	Address of Well Location;	f unknown, distance	Glob	al Positioning	g System (GPS) in	formation:			
	from nearest town or intersection: If at owner's address, check here .					Latitude: .N39.19187 (in decimal degrees)				
Fro	From Goodland 9 mi. S 1/4 mi W					Longitude: W101.73356 (in decimal degrees)				
				Detu	Elevation:					
	Harian House						Collection Method:			
	RR#, Street Address, Box #: 3691 S Highway 27 City, State, ZIP Code : Coodland KS 67735					✓ GPS unit (Make/Model: Garmin GPS 5				
City	, state,	En Code : Goodlar	nd, KS 67735			Digital Map/Ph	oto, 🔲 Topographi	c Map, Land Survey		
3 LOC	CATE W	ELL		···			3 m, 3-5 m,	5-15 m, □ >15 m		
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 44 ft.									
SEC	SCHON BOX: Depth(s) Groundwater Encountered (1) 22 ft (2)									
	WELL 5 STATIC WATER LEVELtt. below land surface measured on mo/day/yr 4/15/13									
	Tump test data: Well water was 25 Higher 1 house numerical 25									
w N	EST. YIELD 50									
''	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
8	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Oil field water supply Dewatering Other (Specify below)									
	Industrial Domestic-lawn & garden Monitoring well									
	was a chemical/bacteriological sample submitted to Department? \tag{7} \text{ No}									
	S If yes, mo/day/yr sample was submitted									
water well disinfected? V Yes No										
5 TYPE OF CASING USED: Steel PVC Other										
CASIN	CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter 5										
Casing height above land surface. 24 in., Weight 2.81 lbs./ft., Wall thickness or gauge No265 TYPE OF SCREEN OR PERFORATION MATERIAL:										
Brass Galvanized Steel None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot										
Continuous slot										
From ft. to ft., From ft. to ft. to ft.										
GRAVEL FACK INTERVALS: From										
rrom trio trion a l										
GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 0 ft. to 22 ft., From ft. to ft. From ft. to ft. What is the pearest source of possible contemporation:										
Orout II	itoi vais.	110m . S It. 10	 π ron	1	ft. to	ft.,	From	ft. toft.		
What is the nearest source of possible contamination: Septic tank Livestock pens Insecticide storage Other (specify below)										
Sewer lines										
Dira	Watertig	ht sewer lines	t	Fertilizer s		Oil well/gas	s well			
FROM	TO	LITHOLOGI	CLOC	. Distance		ell1.2.mi		• • • • • • • • • • • • • • • • • • • •		
0	28	sandy clay	CLOG	FROM	TO	LITHO, LC	OG (cont.) <u>or</u> PLU	GGING INTERVALS		
28	38	sand/gravel								
38	44	shale								
								·		
		the state of the s								
7 CONTRACTORIS OR LANDOWNERS GERMAN										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\subseteq \) constructed, \(\subseteq \) reconstructed, or \(\subseteq \) plugged										
under my jurisdiction and was completed on (mo/day/year) .04/15/13 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 213 This Water Well Record was completed on (mo/day/year) 5/1/13 under the business name of Kemp's Well Service by (signature)										
(1111110, 011	ao, pinik, n	ransas Debai unem on rieann a	ua e nvironment. Bureau a	at Water (Jean)	anni Cantin	1000 CW I I	l Ou O 'u 400 m			
http://www	v.kdheks.g	5524. Send one copy to WATE ov/waterwell/index.html.	A WELL UWNER and r	etain one for y	our recor	ds. Include fee	of \$5.00 for each con	structed well. Vi sit us at		
SSA 82a-1212 Check: ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy										

Marin Barrier