USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

 Location of well: 	County	Fraction Center o	f	1/4 4		Township number Range number T 10 S R 40 E
	Sherman	SE1/4 SE 1/4 SW	1/4			
4 West, 1-3/4, south of Goodland, Kansas R.R. or				where of well: Emig, Emig, Emig, Emig, & Harper or street: RR # 1 state, zip code: Goodland, Kansas 67735		
4. Locate with "X" i		Sketch map:				6. Bore hole dia. 30 in. Completion date 6-14-7 Well depth 243 ft. 7 Cable tool Rotary Driven Dug
Center of SW 1/4,				. 40		B. Use: Domestic Public supply Industry Lawn Oil field water Other
S 1 → 1 Mi 5. Type and color of	ile ————————————————————————————————————		· • • • • • • • • • • • • • • • • • • •	F	.	9. Casing: Material <u>Steet</u> Height: Above or below Threaded <u>Welded X</u> Surface <u>12</u> in. RMP <u>PVC</u> Weight <u>36</u> lbs./ft. Dia in. to <u>243</u> ft. depth Wall Thickness: inches or Dia 16 in. to 243ft. depth gage No. <u>219</u>
3. Type and color of	morera			From	То	10. Screen: Manufacturer's name
clay sand			<u></u>	0	117	Slot/gauze 2 ¹¹ Length 135
medium sands loose clean				117	131	Set between 108 ft. and 243 ft.
sandy cla	У			131	150	Gravel pack? Yes_Size range of material3/8
bentonite				150	180	11. Static water level: mo./day/yr. 11.0 ft. below land surface Date $6-14-76$
sandy clay and rock				180	199	12. Pumping level below land surfaces: 230 ft. after 5 hrs. pumping 970 g.p.m.
sandy clay rock and sand streaks				199	208	
good medium loose clean				208	225	13. Water sample submitted: NO mo./day/yr.
soapstone				225	234	Yes No Date 14. Well head completion:
blue				234	243	Pitless adapter
	BROOK	735				15. Well grouted? <u>Yes</u> With: <u>x</u> Neat cement Bentonite Concrete Depth: From G. ft. to G.
						16. Nearest source of possible contamination: none ft Direction Type
	,					Well disinfected upon completion? Yes No
						17. Pump: Manufacturer's name Byron Jackson Tohn Deare 120
	·					Model number John Deer p. 120 Volts Length of drop pipe 230 ft. capacity 970g.p.m.
						Type:SubmersibleX_Turbine
	(Use a second sl	neet if needed)				Jet Reciprocating Other
18. Elevation: Topography: Hill	19. Remarks:	5 (TUPO)				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Northwest Drilling Co. Inc. 2 Business name License No. Address BOX 11, Goodland, Ks. 677