USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | | | | т | | | eka, Karisas 00020 | | |
|--|--|----------|----------------|------------------------------|---|---|--|--|--|
| 1. Location of well: | County | Fraction | Section number | | number | Township number | Range number | | |
| Sherman SE 1/4 NE 1/4 N | | E 1/4 5 | | | T 10 s | _R 42 | E/W | | |
| 2. Distance and direction from nearest town or city: Kanorado, KS | | | | | l: | Delbert Walt | | | |
| Street address of well location if in city: 8 s. ½ e. R.R. or City, sh | | | | r street: tate, zip code: | | Quinter, KS 67752 | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia . 36 in . Completion date Well depth 264 ft . 5-25-79 | | | |
| | <u> </u> | | | | | 7 Cable tool Rotary | | | |
| NW | NE-X | | | | | Hollow rod Jetted | | rse rotary | |
| | - E | | | | | 8. Use: Domestic P | | | |
| 11 1 1 | | | | | | | Air conditioning Sta Dil field water Oi | | |
| sw | SE | | | | | 9. Casing: Material Stee | | elow | |
| | | | | | | Threaded Welded X RMP PVC | , ,, | 7_lbs./ft. | |
| 1 → 1 Mi | ile ———————————————————————————————————— | | | 7 | | Dia. 16 in. to 264 ft. de | oth Wall Thickness: in | ches or | |
| 5. Type and color of | material | | | From | То | Dia in. to ft. dep 10. Screen: _Manufacturer's | | 219 | |
| C1ay | | | | 0 | 50 | Johnson | | | |
| Sand & Gr | 1 | | | <u> </u> | 75 | Type Wire Wrapped Slot/gauze 100 | | | |
| | | | | 50 | | Set between 254 Perf Brown 194 | _ft. and264 | ft. | |
| Sandy Cla | ay | | | 75 | 984 | Gravel pack?X_ Size ro | | 50% x5/8 | |
| Sandstone | 2 | | | 98 | 103 | 11. Static water level:ft. below land su | 5-T(| J <u>do</u> y/gr. | |
| Sandy Cla | ıÿ | | | 103 | 1311 | 12. Pumping level below land 63 ft. after 2 | | | |
| | | | 131 | 135 | ft. after hrs. purpoing g.p.m. Estimated maximum yield g.p.m. | | | | |
| Sandstone Sandy Clay w Sanstone Streaks | | | 135 | 166 | | | | | |
| Sandstone | | | | 166 | 190 | Yes X No | Date | / ddy/ y/ . | |
| Dandscone | | | | 100 | 170 | 14. Well head completion: Pitless adapter | 12 Inches above | | |
| Coarse Sand | | | 190 | 196 | 15. Well grouted? Yes | | | | |
| Coarse Sand Clay | | | 196 | 198 | With: X Neat cement | βentonite (| Concrete 4 | | |
| Coores | and | | | 198 | 207 | 16. Nearest source of possib | le contamination: | $-\!\!\!\!-\!$ | |
| Coarse Sa | 311U | | | | 207 | ft. <u>5300</u> Direction | S Type Fai | xr ∣ | |
| Clay | | | 207 | 209 | 17. Pump: Not installed | | | | |
| Coarse Sand & Gravel | | | 209 | 218 | Manufacturer's name $\frac{F}{12DOL}$ | Loway HP 110 Vol | <i>q</i> 0 | | |
| Sandstone | | | 218 | 220 | Length of drop pipe25 | | | | |
| Clay | | | | 220 | 231 | Type: Submersible | <u>X</u> Turbine | , _ | |
| (Use a second sheet if needed) (Cont td) | | | | | | Jet Centrifugal | Recipro | ocating S | |
| 18. Elevation: | 19. Remarks: 3R0 | CX Z1,Z' | | | | 20. Water well contractor's This well was drilled under n | | ° C | |
| Tanamanh | . , , , , , | - | | | | is true to the best of my know | wledge and belief. | _ \ | |
| Topography: | | | | | | Western Well Business name | | . 245 > n | |
| Slope | | | | | | Address Box 852 | | 67701 | |
| Upland Valley | | | | | | Signed Authorized re | presentative Date | 1-13-12 | |

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

| | | | | | | lopei | ka, Kansas 66620 | |
|---|--------------------|---|----------------|---|-----------------|---|--|--|
| 1. Location of well: | | | Section number | | Township number | | | |
| Location of well: | | 1/4 1/4 | 1/4 | | | T S | R | E/W |
| Street address of well location if in city: | | | | Owner of well: R. or street: y, state, zip code: (Cont'd) | | | | |
| 4. Locate with "X" i | 1 NE 1 SE | Sketch map: | | | | 6. Bore hole dia in. Well depth ft. 7 Cable tool Rotary Hollow rod Jetted 8. Use: Domestic Pul Irrigation Air Lawn Oil 9. Casing: Material Threaded Welded RMP PVC Dia in. to ft. dept | Driven Du Bored Re blic supply ! conditioning ! field water ! Height: Above or Surface ! Weight ! | g verse rotary ndustry Stock Other belowinlbs./ft. |
| 5. Type and color of | | (Cont'd) |) | From | То | 10. Screen: Manufacturer's no | | |
| Medium Co | oarse Sand | | | 231 | 240 | Туре | Dia | |
| Clay | | *************************************** | | 240 | 243 | Slot/gauze Set betweenft. ar | ft. and | ft. |
| Coarse Sa | and | | | 243 | 248 | Gravel pack? Size ran | ge of material | |
| Clay | | | | 248 | 256 | 11. Static water level:ft, below land surf | | o./day/yr. |
| Coarse S | and & Gravel | - W-00-1 | | 256 | 262 | 12. Pumping level below land | | a.s.m |
| Shale | | | | 262 | 275 | ft. after hr | rs.pumping | g.p.m. |
| | | | | | | Estimated maximum yield | | |
| | | | | | - | Yes No D 14. Well head completion: Pitless adapter 15. Well grouted? | Inches abov | e grade |
| | | | | | | With: Neat cement Depth: From ft. to 16. Nearest source of possible | ft. | Concrete |
| | | * *** | | | | ft Direction Well disinfected upon complet | | No |
| - | 4 | | | | | 17. Pump: Manufacturer's name | Not installed | |
| | | | | | | Length of drop pipe | HP V | 1 |
| | | | | | | Type: Submersible Jet | Turbi Recin | ne rocatina |
| | (Use a second s | neet if needed) | | | | Centrifugal | Othe | ٠, |
| Topography: — Hill — Slope — Upland — Valley | 19. Remarks: | | | | | 20. Water well contractor's control of the self was drilled under my is true to the best of my knowl with the best of my knowl with the best of my knowl with the business name and business and business Address Authorized representations. | jurisdiction and the edge and belief. Frug Colby Kc Law Dat | 145 icense No. 6770 e <u>17-25</u> |