



USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82g-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: Ellis		County Ellis		Fraction SW 1/4 SE 1/4 SE 1/4		Section number 22		Township number 11S		Range number 16		E/W E/W					
2. Distance and direction from nearest town or city: 7 miles South and 3 West of Natoma Kans.						3. Owner of well: Delmar Chrisler R.R. #1 Natoma, Kansas 67651											
4. Locate with "X" in section below: 						Sketch map: 						6. Bore hole dia. 10 in. Completion date 7/20/77 Well depth 60 ft.					
5. Type and color of material						From		To		7. <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary							
Black top soil						0		5		8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other							
Yellow clay and rock						5		30		9. Casing: Material PVC Height: Above or below Threaded Welded <input checked="" type="checkbox"/> Surface 18 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1 1/2 lbs./ft. Dia. 5 in. to 60 ft. depth Wall Thickness: inches or Dia. 5 in. to 60 ft. depth gage No. 250							
Sand and rock						30		40		10. Screen: Manufacturer's name Slotted with saw Type slots Dia. 5" Slot/ 1/16 Length 15' Set between 45 ft. and 55 ft. Gravel pack? yes Size range of material 1/8"							
Grey Clay						40		45		11. Static water level: 31 mo./day/yr. 31 ft. below land surface Date 7/19/77							
Good white gravel and rock						45		50		12. Pumping level below land surfaces: 30 ft. after 4 hrs. pumping 9 g.p.m. 30 ft. after 4 hrs. pumping 9 g.p.m. Estimated maximum yield 23 g.p.m.							
Grey and black shale						50		60		13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date							
										14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 18 inches above grade							
										15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.							
										16. Nearest source of possible contamination: cess-pool ft. 300 Direction NW Type cess-pool Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No							
										17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other							
18. Elevation:						19. Remarks: Owner agrees to use pitless adapter and put in curb.						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Oscar Rush Water Well Service Business name Natoma, Ks. License No. 310 Address Oscar Rush Signed Oscar Rush Date 8/14/77 Authorized representative					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5