WATER WELL RECORD		Form WWC-5		Div	Division of Water Resources App. No.					
1 LOCATION OF WATER WELL:		Fraction		Section	Section Number Township No.			Range Number		
County: Pottawatomie			1/4 Near1/4 CTR 1/4 SE 1/4			T 10 S	R 9	KE []W	
Street/Rural Address of Well Location; if unknown, distance & direction						System (GPS) in				
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)					
1/2 mile NE of St. George, KS					Longitude: (in decimal degrees)					
					Elevation: Datum: □ WGS 84, □ NAD 83, □ NAD 27					
2 WATER WELL OWNER: Jerry Humbert					Collection Method:					
RR#, Street Address, Box #: 520 McDowell Creek Rd.					GPS unit (Make/Model:)					
City, State, ZIP Code : Manhattan, KS 66502					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m					
3 LOCATE WELL				Est. A	ccuracy: [] <	3 m, [3-5 m, [5-15 m, L	_] >15 m		
WITH AN "X" IN	4 DEPTH OF C	COMPLETED WELL	L110)	ft.					
SECTION BOX:	X: Depth(s) Groundwater Encountered (1)								ft.	
N	WELL'S STATIC WATER LEVEL39ft. below land surface measured on mo/day/yr10/1./10									
		ft. after hours pumping gpm								
NW NE	ft.	after	hours pum	ping	gr	m				
W E			to		13					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify belo								***/		
SW SW Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well										
Was a chemical/bacteriological sample submitted to Department? Yes X No										
S If yes, mo/day/yr sample was submitted										
1 mile Water well disinfected?										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: XX Glued Clamped Welded Threaded										
Casing diameter5 in. to30 ft., Diameter ft., Diameter ft.,										
Casing height above land surface1.2										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot XXMill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)										
SCREEN-PERFORATED INTERVALS: From 30 ft. to 110 ft., From ft. to ft.										
From										
From										
6 GROUT MATERIAL: Neat cement Cement grout XX Bentonite Other										
Grout Intervals: From										
What is the nearest source of possible contamination:										
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well										
Sewer lines										
Direction from well										
FROM TO	LITHOLOG		FROM	TO		OG (cont.) <u>or</u> PLU				
	Topsoil		98	120	Shale, g	gray				
1 1	Brown Clay									
1 1 -	tan clay		<u> </u>							
	tone (fractu	res)								
	, gray tone (fractu	rogl								
	, gray	TC9)								
	, gray tone, (fract	ures)	 							
	, gray	urco)								
96 98 Limestone (fractures)										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was x constructed, \(\subseteq \) reconstructed, or \(\subseteq \) plugged										
under my jurisdiction and was completed on (mo/day/year)10/11/10 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No138 This Water Well Record was completed of (190/day/year)10/.25/.10										
under the business name of Peterson Irrigation, Inc. by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copie									·····	
INSTRUCTIONS: Use typew (white, blue, pink) to Kansas I	riter or ball point pen	and Environment Bureau	Y and <u>PRINT</u> c	learly. Ple	ase fill in blank	s and check the correct	et answers.	Send three	copies	
Telephone 785-296-5522. Ser										
http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212										