

1 LOCATION OF WATER WELL: County: Ellis		Fraction NW ¼ SE ¼ SE ¼	Section Number 11	Township Number T 11 S	Range Number R 17 EW
Distance and direction from nearest town or city street address of well if located within city? 4 mi. E of Turkville					
2 WATER WELL OWNER: National Cooperative Refinery Association					
RR#, St. Address, Box # : P.O. Box 1404			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : McPherson, Kansas 67460			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: 20.5 ft. below land surface measured on mo/day/yr 3/25/2009			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield: NA gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8 in. to 30 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply		8 Air conditioning	
		1 Domestic		3 Feedlot	
		6 Oil field water supply		9 Dewatering	
		2 Irrigation		4 Industrial	
		7 Lawn and garden only		10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
		7 Fiberglass		8 Concrete tile	
Blank casing diameter: 2 in. to 10 ft., Dia. in. to ft., Dia. in. to ft.				CASING JOINTS: Glued Clamped	
Casing height above land surface: 24 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40				Welded Threaded. <input checked="" type="checkbox"/>	
TYPE OF SCREEN OR PERFORATION MATERIAL					
1 Steel		3 Stainless steel		7 PVC	
2 Brass		4 Galvanized steel		8 RMP (SR)	
		6 Concrete tile		9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				11 None (open hole)	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 10 ft. to 30 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 30 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 8 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well?					
How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Silt,			
3	12	Sand,			
12	16	Clay,			
16	29	Sand,			
29	30	Shale,			
MW10 , Abovegrade					
Project Name: NCRA - Bemis North					
GeoCore # 1140 , #					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/25/2009 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527			This Water Well Record was completed on (mo/day/yr) 4/1/2009		
under the business name of GeoCore, Inc.			by (signature) <i>Dale Cobb</i>		

OFFICE USE ONLY

SEC. ¼