

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
County: Ottawa NE 1/4 SE 1/4 SE 1/4 6 T 11 S R 2 KW

Distance and direction from nearest town or city street address of well if located within city?
6 miles North & 1 mile East of Bennington, KS

2 WATER WELL OWNER: Garth Baugh
RR#, St. Address, Box #: 1951 Ivy Rd. Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Minneapolis, KS 67420 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with an 'X' in the SE section]
4 DEPTH OF COMPLETED WELL: 109 ft. ELEVATION:
WELL'S STATIC WATER LEVEL: 63 ft. below land surface measured on 10/23/00
Pump test data: Well water was ... ft. after ... hours pumping ... gpm
Est. Yield 10-20 gpm: Well water was ... ft. after ... hours pumping ... gpm
Bore Hole Diameter: 9 in. to 112 ft., and ... in. to ... ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yrs sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
XPVC 4 ABS 7 Fiberglass Threaded
Blank casing diameter: 5 in. to 99 ft., Dia. in. to ... ft., Dia. in. to ... ft.
Casing height above land surface: 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214
TYPE OF SCREEN OR PERFORATION MATERIAL: X7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot X3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ... ft.
SCREEN-PERFORATED INTERVALS: From 99 ft. to 109 ft., From ... ft. to ... ft.
GRAVEL PACK INTERVALS: From 20 ft. to 109 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout XBentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From ... ft. to ... ft., From ... ft. to ... ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool X Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? West How many feet? 200

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Data includes Topsoil (0-2), Sandrock (2-5), Sandstone (5-112).

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/24/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 138 This Water Well Record was completed on (mo/day/yr) 10/30/00 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson