


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: OTTAWA	SE ¼ SW ¼ SW ¼	9	T 11 S	R 2-W E/W

Distance and direction from nearest town or city street address of well if located within city?
2007 JUSTICE RD.

2 WATER WELL OWNER: GARY SMITH	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 2007 JUSTICE RD.	Application Number:
City, State, ZIP Code : MINNEAPOLIS, KS. 67467	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 72 ft. ELEVATION:
--	--



Depth(s) Groundwater Encountered 1**35**..... ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL**35**..... ft. below land surface measured on mo/day/yr ...~~6-02-05~~.....

Pump test data: Well water was**49**..... ft. after**1**..... hours pumping**20**..... gpm

Est. Yield**40**... gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
9 Dewatering	12 Other (Specify below)	

Was a chemical/bacteriological sample submitted to Department? Yes No **X**.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **X** No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 5 in. to 5.2 ft., Dia in. to ft., Dia in. to ft.	Casing height above land surface 1.6 in., weight 1.60 lbs./ft. Wall thickness or guage No. SDR 2.6		
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS:		From 52 ft. to 72 ft., From ft. to ft.	
GRAVEL PACK INTERVALS:		From 2.5 ft. to 7.2 ft., From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 2.5 ft., From ft. to ft., From ft. to ft.	What is the nearest source of possible contamination:			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? NORTH EAST		How many feet? OVER 100		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	6	CLAY TAN WITH SANDSTONE PEBBLES			
6	13	IRON STONE BROWN			
13	72	SANDSTONE TAN			
72		SHALE GRAY HARD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-2-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 388 This Water Well Record was completed on (mo/day/yr) 6-02-05 under the business name of PESTINGER PUMP SERVICE by (signature) <i>[Signature]</i>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.