WATER WELL RECORD OB8	S Form W	WC-5	Division of Wate	er Resources App. No	).
1 LOCATION OF WATER WELL:	Fraction		Section Number	Township No.	Range Number
County: Harvey	NW 1/4 NW 1/4 NW			T 24 S	R 2 □E ☑W
Street/Rural Address of Well Location			Global Positioning	g System (GPS) in	formation:
from nearest town or intersection: If at owner's address, check here			Latitude: .37° 59' 5.3" (in decimal degrees)  Longitude: .097° 34' 23.6" (in decimal degrees)		
On the southeast of intersection SW 48th St. and 199th St W.			Elevation:		
A WATER WELL OWNER.			<u>Datum</u> : ☐ WGS 84, <b>☑</b> NAD 83, ☐ NAD 27		
2 WATER WELL OWNER: City of Wichita RR#, Street Address, Box #: 455 North Main St.			Collection Method:  GPS unit (Make/Model: Garmin )		
RR#, Street Address, Box #: 455 North Main St. City, State, ZIP Code : Wichita, KS 67202			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
VVICING	3, NO 07202		Est. Accuracy: -	3 m, ☐ 3-5 m, ☐	5-15 m, □ >15 m
3 LOCATE WELL	COMPLETED WEL	т 37	A		
					3)ft
N WELL'S STA	1 1 1				
Pump test data: Well water wasft. after hours pumping gpm					oing gpm
NW NE    TT 1 T-	gpm. Well water				
	meter6in. to R TO BE USED AS:				π. njection well
Domostia	Feedlot				Other (Specify below)
Irrigation	☐ Industrial ☐	Domestic-la	wn & garden 🔲 Mo	onitoring well .Ol	servation
	l/bacteriological sample	submitted to	Department?	Yes 🗹 No	
	o/day/yr sample was sub infected?  Yes		••••••		
				·	
5 TYPE OF CASING USED: Ste	el 🗹 PVC 🔲 (			••••	
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .2					
Casing height above land surface. 24.					
TYPE OF SCREEN OR PERFORATION	NMATERIAL:				
Steel Stainless Steel	<ul><li>✓ PVC</li><li>☐ None used (open h</li></ul>	(L	Other (Specify)		
☐ Brass ☐ Galvanized Steel  SCREEN OR PERFORATION OPENIN	GS ARE:	ole)			
☐ Continuous slot	☐ Gauze wrapped ☐			☐ None (open hole	
Louvered shutter					
SCREEN-PERFORATED INTERVALS:         From					
GRAVEL PACK INTERVALS: From 22					
From					
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other					
Grout Intervals: From 0 ft. to .22 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:  ✓ Septic tank  ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well  Direction from well					
FROM TO LITHOLO	GIC LOG	FROM			GGING INTERVALS
Log attached	010 200	1 11011	Limb. E.	oe (com.) <u>or</u> The	GGITO ITTLACTALS
		<b> </b>			
					•
	LAARNA MININE TO THE TOTAL TO T				
	1.2				
					111111111111111111111111111111111111111
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged					
under my jurisdiction and was completed on (mo/day/year) .10/28/2009 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No755 This Water Well Record was completed on mo/day/ far 12/02/2009					
under the business name of Sargent Drilling by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html	Griffer and	, one lot		+50 IOI OUOH <u>O</u>	Ton. Tion us at

KSA 82a-1212

Check: White Copy, Blue Copy, Pink Copy

## Sargent Irrigation

WELL AND PUMP SERVICE

PO Box 268 Holdrege, NE 68949 825 Brewster Road

Phone: (308) 995-6143

1-800-860-2946

## **TEST HOLE LOG**

CUSTOMER: Wichita, KS

WELL ID: OB 08S

LOCATION: NW 1/4 NW 1/4 NW 1/4, 8-T24S-R2W, Harvey Co., KS

LATITUDE: 37° 59' 5.3" LONGITUDE: 097° 34' 23.6"

FOOTAGES: 5163 feet from the South section line and 5134 feet from the East section line.

DATE: 10/28/09

DRILLED BY: Kyle Schoff, Doug Rezac, Cody Hanson

SWL: PWL: GPM:

from feet	- to fe	<u>et</u>
0	5	Top soil and clay
5	20	Coarse sand to medium gravel
20	37	Coarse sand to medium gravel
37	40	Coarse sand to medium gravel with traces of sandy clay

Well Information:

Well depth: 37' Plain casing: 27' Perf. Set: 27' –37' Bore hole: 6" Perf. casing: 10' Gravel: 22-37' Casing size: 2" Slot size: .020" Grout: 0-22'