

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Ellis	Fraction NE 1/4 C 1/4 NE 1/4	Section number 16	Township number T 11 S R 20 E W	Range number
2. Distance and direction from nearest town or city: 3N, 1E, 8N				3. Owner of well: Clarence Lynd		
Street address of well location if in city: of Ellis, Ka.				R.R. or street: R.R. 1 Ellis, Kans.		
				City, state, zip code: 67637		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 9-20-76		
				Well depth 64 ft. 9-20-76		
5. Type and color of material		From	To	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
Top soil		1	8	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input checked="" type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Clay brown		8	17	9. Casing: Material Plt Height Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 18 in. RMP <input checked="" type="checkbox"/> PVC Weight 200 lbs./ft. Dia. 5 in. to 14 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth Gage No. 200235 - 1/2 wall		
Coarse Gravel (white)		17	18	10. Screen: Manufacturer's name Jess & Rawell Type <input type="checkbox"/> Dia. 5 Slot gauge <input type="checkbox"/> Length 101 Set between 14 ft. and 64 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 4-1/2		
Clay Reddish Brown		18	28	11. Static water level: <input type="checkbox"/> mo./day/yr. 22 ft. below land surface Date 9-20-76		
Light silt Black		28	34	12. Pumping level below land surfaces: 24 ft. after 1 hrs. pumping 14 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 15 g.p.m.		
V-F to coarse sand (Brown)		34	45	13. Water sample submitted: <input type="checkbox"/> mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		
Coarse Gravel		45	56	14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 18 inches above grade		
Coarse sand mix with Gravel		56	62	15. Well grouted? <input type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 12 ft.		
Gray shale		62	64	16. Nearest source of possible contamination: ft. 150 Direction N-NE Type Barn Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Fairbank moose Model number <input type="checkbox"/> HP 3 Volts 220 Length of drop pipe 55 ft. capacity 15 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input checked="" type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
		(Use a second sheet if needed)				
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Luce Water Well Drilling Business name 503 Monroe License No. 276 Address John Luce Date 10-1-76 Authorized representative		
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						

T 11 S R 20 E W
 NE 1/4 C 1/4 NE 1/4
 Sec 16