

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number	
County: TREJO	SE 1/4 SE 1/4 NW 1/4	7	T 11 S	R 23 E/W	
Distance and direction from nearest town or city street address of well if located within city? 6 N 4 E 1/2 S of Wakarusa Ks					
2 WATER WELL OWNER: John Milar					
RR#, St. Address, Box # : City, State, ZIP Code : Wakarusa Ks			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 30 22 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 22 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10 gpm: Well water was ft. after hours pumping gpm			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well STOCK			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		5 Wrought iron		8 Concrete tile	
3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)	
4 ABS		7 Fiberglass		CASING JOINTS: Glued X Clamped	
6 PVC				Welded	
				Threaded	
Blank casing diameter 5 in. to 20 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 250 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel		5 Fiberglass	
2 Brass		4 Galvanized Steel		6 Concrete tile	
				7 RMP (SR)	
				8 ABS	
				10 Asbestos-Cement	
				11 Other (Specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot		5 Guazed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
				11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 30 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below) River	
Direction from well? South				How many feet? 100	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	Top soil			
10	22	Sandy Clay			
22	29	m. sand			
29	30	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1)** constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **1-6-12** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **376** This Water Well Record was completed on (mo/day/yr) **1-22-12** under the business name of **B+R Drilling LLC** by (signature) **Joseph Bestman**