


1 LOCATION OF WATER WELL: County: Trego Fraction NE 1/4 NE 1/4 SE 1/4 Section Number 26 Township Number T 11 S Range Number R 25 E/W

Distance and direction from nearest town or city street address of well if located within city?  
3 East, 2 1/2 North of Collyer, Kansas

2 WATER WELL OWNER: Rex Shearer  
 RR#, St. Address, Box # : RFD  
 City, State, ZIP Code : Collyer, Kansas 67631  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 91 ft. ELEVATION: Upland  
 Depth(s) Groundwater Encountered 1. 76 ft. 2. 75 ft. 3. 6/24/1982 ft.  
 WELL'S STATIC WATER LEVEL 75 ft. below land surface measured on mo/day/yr 6/24/1982  
 Pump test data: Well water was 80 ft. after 1 hours pumping 4 gpm  
 Est. Yield 4 gpm: Well water was 80 ft. after 1 hours pumping 4 gpm  
 Bore Hole Diameter 9 in. to 91 ft., and 91 in. to 91 ft.  
 WELL WATER TO BE USED AS: 1 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No         ; If yes, mo/day/yr sample was sub-  
 mitted Water Well Disinfected? Yes X No         

5 TYPE OF CASING USED: 2 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped           
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded           
2 PVC 4 ABS 7 Fiberglass Threaded           
 Blank casing diameter 5 in. to 71 ft., Dia          in. to          ft., Dia          in. to          ft.  
 Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or gauge No. .21  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 7 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)           
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)           
 SCREEN-PERFORATED INTERVALS: From 71 ft. to 91 ft., From          ft. to          ft.  
 From          ft. to          ft., From          ft. to          ft.  
 GRAVEL PACK INTERVALS: From 55 ft. to 91 ft., From          ft. to          ft.  
 From          ft. to          ft., From          ft. to          ft.

6 GROUT MATERIAL: 1 1 Neat cement 2 Cement grout 3 Bentonite 4 Other           
 Grout Intervals: From 0 ft. to 10 ft., From          ft. to          ft., From          ft. to          ft.  
 What is the nearest source of possible contamination: NONE 10 Livestock pens 14 Abandoned water well  
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	50	Brown clay			
50	82	Sand and clay			
82	87	Brown clay			
87	91	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 24, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 199 This Water Well Record was completed on (mo/day/yr) August 4, 1982 under the business name of Karst Water Well Service by (signature) MB Karst

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
 T  
 R  
 25  
 E/W  
 SEC. 26  
 NE 1/4  
 NE 1/4  
 SE 1/4