				ER WELL RECORD		C-5 KSA 8		
		ATER WELL:	Fraction	NINY (/ NINY		ection Numb	•	
County:		- franc	NW ½		<u> </u>	32 b/2	T 11 S	R 26 BW
I-70 and	d K-212	- Quinter, KS		address of well if locate	ea within ci	.y r		
		WNER: Jim Gr						
RR#, St. A	ddress, Bo	x# : P.O. Bo					_	Division of Water Resources
City, State,	ZP Code	: Quinte	r, Kansas 67'				Application Number:	
		LOCATION						
WITHA		ECTION BOX: N	Depth(s) Groun	dwater Encountered 1			ft. 2	. ft. 3 ft.
∓ ⊠			WELL'S STATI	C WATER LEVEL	f	t, below land	I surface measured on mo.	/day/yr
	·		Pum	p test data: Well water	was	N.A ft.	after hour	s pumping gpm
-	- NW	NE	Est. Yield N	Agpm: Wellwate	rwas	ft.	. after houi	rs pumping gpm
₩ ¥	İ	!	Bore Hole Dian	neter \$ in. to	10) <u>()</u>	., and	in. to
- w ⊢		│	WELL WATER	TO BE USED AS: 5	Public water	er supply	8 Air conditioning	11 Injection well 12 Other (Specify below)
1	<u>.j.</u> .	1 <u>i</u> 1	1 Domestic			iter supply		(12) Other (Specify below)
	- sw	† - \$E	2 Irrigation					Air Sparging
↓	I	!!!		al/bacteriological sample	e submitted			fyes, mo/day/yr sample was
<u></u>		S	submitted				Nater Well Disinfected? Y	es No V
5 TYPE C	OF BLANK	CASING USED:		5 Wrought iron	8 Con	crete tile		Glued Clamped
	eel	3 RMP (SI	R)	6 Asbestos-Cement	9 Othe	er (specify b	-	Welded
(2)P\		4 ABS		7 Fiberglass				Threaded 🗸
Blank casir	ng diamete	r 2 <i></i> .	in. to	3 ft., Dia	in.	to	ft., Dia	in. to ft.
Casing hei	ght above l	and surface	0	.in., weight			s./ft. Wall thickness or ga	uge No Sch. 40
TYPE OF S	SCREEN C	R PERFORATIO	N MATERIAL		(7) P	VC	10 Asbestos	-cement
1 Ste	eel	3 Stainless	s steel	5 Fiberglass	8 R	MP (SR)	11 Other (sp	ecify)
2 Br	ass	4 Galvaniz	red steel	6 Concrete tile	9 A	BS	12 None use	ed (open hole)
SCREEN C	OR PERFO	RATION OPENIN	IGS ARE:	5 Gauze	ed wrapped		8 Saw cut	11 None (open hole)
	ontinuous s		/ill slot		wrapped		9 Drilled holes	`` '
2 Lo	uvered sho	utter 4 K	(ey punched	7 Torch	cut		10 Other (specify)	
SCREEN-F	PERFORAT	ED INTERVALS:						ft. to ft.
			From	ft. to		ft.,	From	ft. to ft. ,
G	RAVEL PA	CK INTERVALS:		83	93	ft.,	From	ft. to ft.
			From	ft. to	· · · <u>· · · · · ·</u>	ft.,	From	ft. to ft.
	MATERIA			2 Cement grout	(3)Ben			
Grout Inter	vals: Fro	m <u>. 0</u>	.ft. to	ft., From	81 ft	. to	3 ft, From	ft. to ft.
What is the	e nearest s	ource of possible	contamination:			10 Li	vestock pens	14 Abandoned water well
1 Septi	ic tank	4 Late	ral lines	7 Pit privy		11 Fu	uel storage	15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer stor							ertilizer storage	16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage UST Basin								UST Basin
Direction f	rom well?	N				How n	nany feet? 100	
FROM	TO		LITHOLOGIC	LOG	FROM	TO		NG INTERVALS
0	0.17	Asphalt,			76	77	Caliche, White to B	
0.17	6	Clay, Dark B	<u> Brown to Brov</u>	vn	77	82	Sand, Brown to Tan	
6	12	Silt, Light Br	rown to Tan		82	87	Sand, Brown to Tan	
12	21	Silt, Brown t	o Buff		87	100	Sand, Brown to Tan	
21	27	Silt, Cream t	o Buff					
27	32	Sand, Red Bi	rown to Tan					
32	37	Sand, Red B	rown to Tan					
37	42	Sand, Red Bi	rown to Buff					
42	47	Silt, Red Bro	ME					
47	52	Silt, Red Bro						
52	57	Silt, Brown t						
57	62	Silt, Brown t						
62	67	Sand, Light l					ASW , Flushmount	
67	72	Silt, Red Bro					Project Name: Graham 6	6 Service
72	76	Silt, Red Bro					GeoCore # 288, KDHE #	U6 032 513
_				ION: This water well wa	s (1) cone	tructed (2)	econstructed, or (3) plugg	
		n (mo/day/year)		3/28/96				of my knowledge and belief.
		n (mo/day/year) Contractor's Licer					as completed on (mo/day/	, , , , , , ,
	business n			re Services, Inc.			nature)	2M
					early Di			mr. Sandtan thus sania to V
							one to WATER WELL OWNER a	vers. Send top three copies to Kansas and retain one for your records.