

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Gove		NW ¼ NW ¼ NW ¼	32	T 11 S	R 26 E/W
Distance and direction from nearest town or city street address of well if located within city? I-70 and Hwy K212 - Quinter, Kansas					
2 WATER WELL OWNER: Jim Graham					
RR#, St. Address, Box # : P.O. Box 398			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Quinter, Kansas 67752			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 95 ft. ELEVATION: 2660.3			
		Depth(s) Groundwater Encountered 1. 999 ft. 2. 999 ft. 3. 999 ft.			
		WELL'S STATIC WATER LEVEL 999 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm			
		Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm			
		Bore Hole Diameter 8 in. to 95 ft., and 95 in. to 95 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		Air Sparging Well			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input type="checkbox"/> Clamped <input type="checkbox"/>
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <input type="checkbox"/>
			7 Fiberglass		Threaded <input checked="" type="checkbox"/>
Blank casing diameter 2 in. to 93 ft., Dia 93 in. to 93 ft., Dia 93 in. to 93 ft.					
Casing height above land surface -5.16 in., weight Sch. 40 lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 93 ft. to 95 ft., From 93 ft. to 95 ft., From 93 ft. to 95 ft.					
GRAVEL PACK INTERVALS: From 91 ft. to 95 ft., From 91 ft. to 95 ft., From 91 ft. to 95 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 76 ft., From 76 ft. to 91 ft., From 91 ft. to 91 ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	UST Basin
Direction from well? SE		How many feet? 90			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Asphalt,			
0.5	3	Clay, Dark Brown			
3	16	Clay, Light Brown			
16	18	Clay, Brown			
18	28	Clay, Light Tan			
28	41	Sand, Red Brown to Buff			
41	58	Sand, Red Brown			
58	65	Sand, White			
65	80	Sand, White			
80	94	Sand, White Gray			
94	95	Sand, Light Brown Buff			
					ASP4, Tag # 00175010, Flushmount
					Project Name: Graham 66 Service
					GeoCore # 288, KDHE # U6 032 513
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/6/97 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527		This Water Well Record was completed on (mo/day/yr) 2/4/97			
under the business name of GeoCore Services, Inc.		by (signature) <i>[Signature]</i>			

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4