


1 LOCATION OF WATER WELL: County: Gove Fraction: SW 1/4 NE 1/4 SE 1/4 Section Number: 27 Township Number: T 11 S Range Number: R 26 E

Distance and direction from nearest town or city street address of well if located within city? 2 E of Quinter

2 WATER WELL OWNER: Marie Neher RR#, St. Address, Box #: Quinter, Ks. 67752 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 112 ft. ELEVATION: 80 ft. Depth(s) Groundwater Encountered 1. 80 ft. 2. 80 ft. 3. 80 ft. WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr Pump test data: Well water was 1.4 gpm; Well water was 112 ft. after 9 hours pumping 112 gpm Est. Yield 1.4 gpm; Well water was 112 ft. after 9 hours pumping 112 gpm Bore Hole Diameter 9 in. to 112 ft., and 9 in. to 112 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded ② PVC 4 ABS 7 Fiberglass 9 Other (specify below) Blank casing diameter 5 in. to 112 ft., Dia. 5 in. to 112 ft., Dia. Casing height above land surface 9 in., weight 250 lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: ① Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 102 ft. to 112 ft., From 102 ft. to 112 ft., From 102 ft. to 112 ft. GRAVEL PACK INTERVALS: From 80 ft. to 112 ft., From 80 ft. to 112 ft., From 80 ft. to 112 ft.

6 GROUT MATERIAL: ① Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Dam 13 Insecticide storage How many feet? 600

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	17	Topsoil			
17	70	Sandy Clay			
70	79	M. Gravel			
79	106	Sandy Clay			
106	111	Rock			
111	112	Chert			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 376 This Water Well Record was completed on (mo/day/yr) 6-25-86 under the business name of B & B Drilling by (signature) Joseph Bestman

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4