


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 32 Township Number T 11 S Range Number R 26 E W
 County: Gove Distance and direction from nearest town or city street address of well if located within city?

I 70

2 WATER WELL OWNER: Jimmy Graham
 RR#, St. Address, Box #: P. O. Box 398 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Quinter, Ks. 67752 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 78.98 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 in. to 100 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X
 Blank casing diameter: 4 in. to 60 ft. Dia. 2.071 in. to ft. Dia in. to ft.
 Casing height above land surface: in. weight 2.071 lbs./ft. Wall thickness or gauge No. .237

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 100 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 58 ft. to 100 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 55 3 Bentonite 58 4 Other
 Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage Removed Fuel Storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.6	Asphalt	95	100	Sandy Clay
.6	14	Loess			
14	20	Clay & Caliche Strks.			
20	25	Sandy Clay w/Sand & Caliche			
25	27	Med. Sand & Gravel w/s.Clay			
27	35	Clay w/Sand Mix			
35	45	Sandy Clay w/Caliche Strks.			
45	50	Sandy Clay w/Sand & Cal. St.			
50	64	Light Brown Sticky Clay			
64	66	Cemented Sand & Caliche			
66	68	Sand			
68	75	Sandy Clay w/Caliche/s.Sand			
75	78	Sandy Clay			
78	80	Sand w/Clay Strks.			
80	95	Fine to Med. Sand & Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-15-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 5-31-94 under the business name of Woofter Pump & Well, Inc. by (signature) *Jimmy Graham*

OFFICE USE ONLY

T

R

EM

SEC

1/4

1/4

1/4