

OFFICE USE ONLY
T
R
EW
SEC
1/4
1/4
1/4

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SW 1/4 Section Number 34 Township Number T 11 S Range Number R 26 EW

Distance and direction from nearest town or city street address of well if located within city?
2 miles east, 1 1/2 miles south of Quinter, Ks.

2 WATER WELL OWNER: Quinstar Corporation
RR#, St. Address, Box #: 300 Factory Rd. Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Quinter, Ks. 67738 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SW section of the NW quarter. A 1-mile scale bar is shown.]

4 DEPTH OF COMPLETED WELL: 96.6 ft. ELEVATION: 96.6 ft.
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 58' 10" ft. below land surface measured on mo/day/yr
Pump test data: Well water was . ft. after . hours pumping . gpm
Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
Bore Hole Diameter: 6 1/4 in. to 96.6 ft., and . in. to . ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes . No X .; If yes, mo/day/yr sample was submitted .
Water Well Disinfected? Yes . No X .

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued . X . Clamped . Welded . Threaded .
Blank casing diameter . 2 in. to 66.6 ft., Dia . in. to . ft., Dia . in. to . ft.
Casing height above land surface . 24 in., weight . 69 lbs./ft. Wall thickness or gauge No. . 154
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From . 66.6 ft. to 96.6 ft., From . ft. to . ft.
GRAVEL PACK INTERVALS: From . 20 ft. to 96.6 ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug
Grout Intervals: From . 20 ft. to 0 ft., From . ft. to . ft., From . ft. to . ft.
What is the nearest source of possible contamination: None 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Surface	95	96.6	Flint
3	13	Clay			
13	35	Clay & Caliche			
35	39	Caliche & Clay			
39	48	Brown Clay (sticky)			
48	53	Med. sand			
53	56	Clay			
56	68	Med. sand & gravel			
68	69	Caliche			
69	70	Clay-sandy with cemented strks.			
70	81	Clay			
81	85	Med. sand			
85	87	Cemented sand			
87	92	Clay & cemented sand			
92	95	Med. sand & gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-31-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 394 This Water Well Record was completed on (mo/day/yr) 10-1-92(Correction) under the business name of WOOFER PUMP & WELL by (signature) Walter Woofar