WATER WELL RECORD			Form W	WC-5	Division of Wat	er Resources App. N	o, L	
	LOCATION OF WATER WELL: County: GOVE		Fraction  1/4 NW 1/4 NW	/ ¼ SE ¼	Section Number 30		Range Number R 27 ☐E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here								
			•	Longitude: (in decimal degrees)				
3-1/2 MI SOUTH OF PARK 3/4 MI EAST 1/4 MI NORTH					Elevation:			
A IVATED WELL OWNER.					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: 1 & F FARMS LLC					Collection Method:			
RR#, Street Address, Box #: P.O. BOX 87					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City,	, State, ZIP Co	de : GRAINF	FIELD, KS 67737		Digital Map/P	hoto, Topographi	c Map, Land Survey	
					Est. Accuracy:	<3 m,	5-15 m,  >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 96								
	H AN "X" IN	"IN 4 DEPTH OF COMPLETED WELL 39						
SECI	TION BOX:	Depth(s) Groundwater Encountered (1)						
	14	WELL'S STATIC WATER LEVEL						
] ] 1	Pump test data: Well water wasft. after							
EST. YIELD.15gpm. Well water wasft. after hours pumping								
w Bore Hole Diameter 8.75 in. to ft., and in. to ft.								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic    Feedlot    Oil field water supply    Dewatering    Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department?  Yes  No								
S If yes, mo/day/yr sample was submitted								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: M Glued Clamped Welded Threaded								
Casing diameter .5								
Casing height above land surface. 24 in., Weight .160 is./ft., Wall thickness or gauge NoSDR.26.								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout 7 Bentonite Other								
Grout Intervals: From .0								
What is the nearest source of nossible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well NONE								
			***************************************		from well			
FROM	ТО	LITHOLOG	IC LOG	FROM	TO LITHO, L	OG (cont.) or PLU	GGING INTERVALS	
		SOIL		<b></b>				
5		WN CLAY						
26		WN CLAY & SANI	)					
30	36 SAN							
36	38 TAN	CLAY						
38		DY CLAY						
67	87 SAN					type, p. 1		
87		Y CLAY W/ SAND						
95		OW / PINK CLAY		<b> </b>				
98				<del>  -</del>				
98   BEDROCK								
under my jurisdiction and was completed on (mo/day/year) .4/5/20.13 and this record is true to the best of my knowledge and belief.								
under my jurisdiction and was completed on (mo/day/year) .4/2/19								
under the business name of AQUA PUMP LLC by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								