

Corrected

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

[ ]

Well ID


MW-101

Original Record  Correction  Change in Well Use

1 LOCATION OF WATER WELL: County: Gove Fraction SW 1/4 NE 1/4 NE 1/4 SW 1/4 Section Number 7 Township Number T 11 S Range Number R 27 E W

2 WELL OWNER: Last Name: ADM Grain First: Business: ADM Grain Address: PO Box 1470 Address: 4666 Faries Parkway City: Decatur State: IL ZIP: 62526 Street or Rural Address where well is located: 504 S Cedar

3 LOCATE WELL WITH "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 128 ft. Depth(s) Groundwater Encountered: 1) 113 ft. 2) 113 ft. 3) Dry Well WELL'S STATIC WATER LEVEL: 113 ft. below land surface, measured on (mo-day-yr) 02/18/2015

5 Latitude: 39.1103 Longitude: 100.3634 Datum: WGS 84 Source for Latitude/Longitude: GPS

6 Elevation: 2745 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household, Lawn & Garden, Livestock, Irrigation, Feedlot, Industrial 5. Public Water Supply, Dewatering, Aquifer Recharge, Monitoring, Environmental Remediation, Air Sparge, Soil Vapor Extraction, Recovery, Injection 10. Oil Field Water Supply, Test Hole, Geothermal, Closed Loop, Open Loop, Surface Discharge, Inj. of Water, Other

Was a chemical/bacteriological sample submitted to KDHE? No If yes, date sample was submitted:

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter: 4 in. to 108 ft. Diameter: in. to ft. Diameter: in. to ft. Casing height above land surface: 0 in. Weight: 2.0710 lbs./ft. Wall thickness or gauge No. 237

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 108 ft. to 128 ft. GRAVEL PACK INTERVALS: From 106 ft. to 128 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 0 ft. to 5 ft. From 5 ft. to 106 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well

Table with 6 columns: 10 FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows include cement, loess, clay w/caiche lenses, fine & med sand w/clay strks, sandy clay w/clay lenses, clay & caiche w/sandy clay strks, fine & med sand w/clay lesnes.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 02/18/2015 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 881 This Water Well Record was completed on (mo-day-year) 02/25/2015 under the business name of Woofter Pump and Well, Inc.