


1 LOCATION OF WATER WELL: County: Moore Fraction: NE 1/4 NE 1/4 SW 1/4 Section Number: 12 Township Number: T 11 S Range Number: R 28 E

Distance and direction from nearest town or city street address of well if located within city? 1 W of Park KS

2 WATER WELL OWNER: Anthony Fieldt RR#, St. Address, Box #: RR 1 City, State, ZIP Code: Park, KS 67751 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 170 ft. ELEVATION: 120 ft. below land surface measured on mo/day/yr

Depth(s) Groundwater Encountered 1. 120 ft. 2. 120 ft. 3. 120 ft.

WELL'S STATIC WATER LEVEL: 120 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 30 gpm. Well water was 9 in. to 170 ft. and 170 in. to 170 ft. after 30 hours pumping. Est. Yield: 30 gpm. Well water was 9 in. to 170 ft. and 170 in. to 170 ft. after 30 hours pumping.

Bore Hole Diameter: 9 in. to 170 ft. and 170 in. to 170 ft.

WELL WATER TO BE USED AS: Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted X Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below)

2 PVC, 4 ABS, 7 Fiberglass

Blank casing diameter: 5 in. to 150 ft. Dia. Casing height above land surface: 12 in., weight: 250 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 10 Asbestos-cement

2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 6 Wire wrapped, 9 Drilled holes

2 Louvered shutter, 4 Key punched, 7 Torch cut, 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 150 ft. to 170 ft. From 150 ft. to 170 ft.

GRAVEL PACK INTERVALS: From 110 ft. to 170 ft. From 110 ft. to 170 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other

Grout Intervals: From 0 ft. to 20 ft. From 0 ft. to 20 ft.

What is the nearest source of possible contamination: 10 Livestock pens, 14 Abandoned water well

1 Septic tank, 4 Lateral lines, 7 Pit privy, 11 Fuel storage, 15 Oil well/Gas well

2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 12 Fertilizer storage, 16 Other (specify below)

3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 13 Insecticide storage

Direction from well? SW How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	28	Top soil			
28	112	S clay			
112	126	Gravel			
126	140	S clay			
140	146	Gravel			
146	160	S clay			
160	169	m Gravel			
169	170	o chie			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-29-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 376 This Water Well Record was completed on (mo/day/yr) 6-23-95 under the business name of B+B Drilling by (signature) Joseph Beckman

OFFICE USE ONLY
T
R
EW
SEC.